

Features

• Nilo is a 360° curve-shaped luminaire with a striking, minimalistic design, perfect for retail, hospitality, and office environments The product can be suspended at different heights to create appealing lighting effects Stand-alone and self contained lighting fixture Aluminium body, opal diffuser, emits direct and indirect lighting Textured black finishing colour Light color temperature: 4000K, neutral white System power: 85W Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation DALI dimmable, 220-240V / 50-60Hz 75% direct, and 25% indirect lighting Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Nominal product dimensions: diameter 1140mmx65mm


Product Overview

Product name	NILO 1200 DIR/INDIR 4K DALI BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Retail, Museums & Galleries
ETIM Class	EC002892
Fixture luminous flux (lm)	9570
Luminaire efficacy (lm/W)	113
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0

NILO 1200 DIR/INDIR 4K DALI BLACK 2050611

Total power consumption (W)	85
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5025768506118
Warranty	5 years
Dimming method	DALI

Photometry



Technical drawings

