



Features

- Ceiling recessed LED Linear luminaire with Louvre + Micro Prismatic Optic, Dimensions: 1154mm x 90mm x 91mm, Direct, White Body, DALI Dimmable (Switch-Dim), Warm White LED (3000K), 3200lm, 27W, 119lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<19, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C, Can be covered with building insulation of Glass wool type


Product Overview

Product name	RANA LINEAR R 3KLM WW LOUV+PRI D
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
General application	Office, Hospitality, Retail, Education
ETIM Class	EC002892
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	118.51
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	27

RANA LINEAR R 3KLM WW LOUV+PRI D
0052356

Electrical protection	Class I
Control gear type	Electronic ballast
Minimum dimming level (%)	1
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5410288523569
Warranty	5 years
Dimming method	DALI
Useful luminous flux (#use)	3200

Photometry



Technical drawings

