

START DOWNLIGHT 205 IP54 SSC01 2150LM 840 DALI
0030376



Features

- Ceiling recessed LED downlight IP54 (from the front), with only 60mm product depth and 205mm cutout. Ideal replacement for 1x42W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Die-cast aluminium body, 20W,4000K, Driver Current: 600mA, CRI80, 74° beam angle, IP54 from the front, IK07, (HxW) 60x205mm, Class 2, 220-240V, SylSmart Standalone Scene enabled . Meets TP(a) requirements.


Product Overview

Product name	START DOWNLIGHT 205 IP54 SSC01 2150LM 840 DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Retail
ETIM Class	EC001744
Fixture luminous flux (lm)	2150
Luminous flux (lm)	2150
Luminaire efficacy (lm/W)	108
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	74
Glare control	< 25
Photobiological Risk Group	RG0

START DOWNLIGHT 205 IP54 SSC01 2150LM 840 DALI 0030376

Total power consumption (W)	20
Electrical protection	Class II
Control gear type	Electronic ballast
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9003
IP rating	IP54/20
IK rating	IK07
Product EAN number	5410288303765
Warranty	5 years
Dimming method	SylSmart SSC
Useful luminous flux (#use)	2150

Photometry



Technical drawings

