

T8 LED UV-A 24" 6.5W 230V TOUGHCOAT **0001689**





Features

• Sylvania T8 LED UV-A tubes in 18" and 24" for flykilling applications• Easy and safe replacement for fluorescent tubes without any rewiring required• LED upgrade for installations with CCG/ magnetic fluorescent ballast using a LED replacement starter (supplied)• Suitable for direct mains operation• Approx. 75% energy saving vs fluorescent originals• Flycatch rate in line with Sylvania Fluo T8 after 180 mins*• Special frosted glass tube does not block UV or degrade intransmission over life• Acid etched glass delivers optimal beam distribution to maximize insect attraction• Optimised UV spectrum to maximize insect attraction• UV-A LED chip with peak emission at 370nm

Product Overview

| Product name | T8 LED UV-A 24" 6.5W 230V TOUGHCOAT |
|---------------------------------|-------------------------------------|
| Technology | LED |
| Lamp shape | Tube, double-ended |
| Cap/Base | G13 |
| Lamp finish | Frosted/Coated |
| Fixture rating | Open |
| General application | SPG |
| Light colour | BL368 Blacklight |
| Colour Variation Initial (SDCM) | N/A |
| Photobiological Risk Group | RG0 |
| Wattage (W) | 6.5 |
| Dimmable | No |
| Product EAN number | 5410288016894 |

Data table

GENERAL DATA



T8 LED UV-A 24" 6.5W 230V TOUGHCOAT

0001689

| Product name | T8 LED UV-A 24" 6.5W 230V TOUGHCOAT |
|---------------------|-------------------------------------|
| Technology | LED |
| Lamp shape | Tube, double-ended |
| Cap/Base | G13 |
| Lamp finish | Frosted/Coated |
| Fixture rating | Open |
| General application | SPG |

OPTICAL DATA

| Light colour | BL368 Blacklight |
|---------------------------------|------------------|
| Colour Variation Initial (SDCM) | N/A |
| Photobiological Risk Group | RG0 |

ELECTRICAL DATA

| Wattage (W) | 6.5 |
|--|---------|
| Current (A) | 25 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Control gear required | No |
| Dimmable | No |
| Inrush Current (A) | 25 |
| Inrush Duration (µs) | 200 |
| Nominal Frequency (Hz) | 50/60Hz |

PHYSICAL DATA

| Weight (kg) | 0.152 |
|-------------|-------|

PACKAGING

| Product EAN number | 5410288016894 |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 64.4 |
| Packaging single width (cm) | 3.5 |
| Packaging single depth (cm) | 3.5 |
| DUN14 (inner) | 15410288016891 |



T8 LED UV-A 24" 6.5W 230V TOUGHCOAT

0001689

| Units per outer package | 25 |
|---------------------------------------|------|
| omis per care passings | |
| Packaging outer length / height (cm) | 66.8 |
| i ackaging outer length i neight (cm) | 00.0 |
| Dealersing autor width (am) | 10.5 |
| Packaging outer width (cm) | 18.5 |
| | 10.5 |
| Packaging outer depth (cm) | 18.5 |

SAFETY DATA

| Special purpose lamp | Yes |
|-------------------------------------|-----|
| Dry applications use only | No |
| Suitable for household illumination | No |