



Features

- IP44 from the front round LED downlight with polycarbonate diffuser with a white bezel. Shallow recess depth (<65mm). Available in 12, 15, 21 & 25W in 150mm, 175mm, 205mm & 225mm cut out sizes. Perfect for up to 2x26W CFL replacement. Includes loop-in loop-out facility for quick installation.


Product Overview

Product name	Insaver HO Topper LED II 175 RO 15W WW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
ETIM Class	EC001744
E-number SE	7465676
Fixture luminous flux (lm)	1500
Luminaire efficacy (lm/W)	100
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	74
Glare control	< 24
Photobiological Risk Group	RG0
Total power consumption (W)	15

Insaver HO Topper LED II 175 RO 15W WW
3033936


Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9010
IP rating	IP44/20
IK rating	IK07
Product EAN number	8711971339366
Warranty	5 years
Dimming method	N/A

Photometry



Insaver HO Topper LED II 175 RO 15W WW
3033936

Technical drawings



Data table

GENERAL DATA

Product name	Insaver HO Topper LED II 175 RO 15W WW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
Operating temperature range (°C)	-10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number SE	7465676
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	1500
----------------------------	------

Insaver HO Topper LED II 175 RO 15W WW 3033936

Luminaire efficacy (lm/W)	100
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	74
Distribution type	Symmetric
Glare control	< 24
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	15
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	390
Inrush Current (A)	7.52
Inrush Duration (µs)	830
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	10
Max. products per 13A C Breaker	14
Max. products per 16A C Breaker	17
Max. products per 20A C Breaker	20

Insaver HO Topper LED II 175 RO 15W WW 3033936

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	74000
Lifespan L90 B10	34000

PHYSICAL DATA

Housing colour	RAL9010
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Height (mm)	55
Nominal Product Diameter (mm)	195
Weight (kg)	0.537
Recessed Depth (mm)	150

PACKAGING

Product EAN number	8711971339366
Packaging single length / height (cm)	22.7
Packaging single width (cm)	22.9
Packaging single depth (cm)	6.2
DUN14 (inner)	18711971339363
Units per outer package	12
Packaging outer length / height (cm)	48.1
Packaging outer width (cm)	48.5
Packaging outer depth (cm)	21.1

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-10-25
Special purpose lamp	No
Dry applications use only	No

SYLVANIA

Insaver HO Topper LED II 175 RO 15W WW
3033936

Suitable for household illumination

No

Light your world