

Features

- Compact, energy efficient and exceptional value LED GU10 lampSame shape and size as halogen GU10 lampCompact Cluster SMD technology enabling high efficiency with halogen lookReduced visible heat sink from the frontAvailable in 36 degree beam angleHigh lumen efficacy15,000 hours average rated life3 years warranty



Product Overview

Product name	RefLED ES50 V6 345LM 840 36 SL5
Technology	LED
Watt (Rated) (W)	4.2
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Wattage (W)	4.2
Power consumption (W)	4.2
Dimmable	No

RefLED ES50 V6 345LM 840 36 SL5
0029168

Average life (Nominal) (h)	15000
Product EAN number	5410288291680
Warranty	3 years
Useful luminous flux (#use)	345

Technical drawings



Data table

GENERAL DATA

Product name	RefLED ES50 V6 345LM 840 36 SL5
Technology	LED
Watt (Rated) (W)	4.2
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959



RefLED ES50 V6 345LM 840 36 SL5
0029168

Warranty	3 years
----------	---------

OPTICAL DATA

Useful luminous flux (#use)	345
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	770
Beam Angle (°)	36
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	4.2
Wattage (W)	4.2
Equivalent watt (W)	50
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	3.9
Inrush Duration (µs)	4100
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	123
Max. products per 16A B Breaker	74

LIFETIME DATA

Lifespan L70 B50	15000
------------------	-------



RefLED ES50 V6 345LM 840 36 SL5
0029168

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Height (mm)	54
Nominal Product Diameter (mm)	50
Weight (kg)	0.093

PACKAGING

Product EAN number	5410288291680
Packaging single length / height (cm)	8.2
Packaging single width (cm)	19.5
Packaging single depth (cm)	5.0
DUN14 (inner)	15410288291687
Units per outer package	6
Packaging outer length / height (cm)	9.6
Packaging outer width (cm)	20.8
Packaging outer depth (cm)	32.5

SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures


Energy label



5
kWh/1000h



2019/2015



5
kWh/1000h



2019/2015