

Concord

NILO 1200 DIR/INDIR 3K DALI WHITE

2050608



Features

• Nilo is a 360° curve-shaped luminaire with a striking, minimalistic design, perfect for retail, hospitality, and office environments The product can be suspended at different heights to create appealing lighting effects Stand-alone and self contained lighting fixture Aluminium body, opal diffuser, emits direct and indirect lighting Textured white finishing colour Light color temperature: 3000K, warm white System power: 85W Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation DALI dimmable, 220-240V / 50-60Hz 75% direct, and 25% indirect lighting Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Nominal product dimensions: diameter 1140mmx65mm

Product Overview

Product name	NILO 1200 DIR/INDIR 3K DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Retail, Museums & Galleries
ETIM Class	EC002892
Fixture luminous flux (lm)	9120
Luminaire efficacy (lm/W)	107
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0


Concord

NILO 1200 DIR/INDIR 3K DALI WHITE

2050608

Total power consumption (W)	85
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5025768506088
Warranty	5 years
Dimming method	DALI

Photometry




Concord

NILO 1200 DIR/INDIR 3K DALI WHITE

2050608

Technical drawings



Data table

GENERAL DATA

Product name	NILO 1200 DIR/INDIR 3K DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Retail, Museums & Galleries
Operating temperature range (°C)	1°C...+25°C
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	9120
Luminaire efficacy (lm/W)	107
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80

NILO 1200 DIR/INDIR 3K DALI WHITE 2050608

Colour Variation Initial (SDCM)	3
Distribution type	Symmetric
Glare control	< 23
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	85
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	7.0
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	1024
Inrush Current (A)	31.2
Inrush Duration (μ s)	182
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	14
Max. products per 13A C Breaker	18
Max. products per 16A C Breaker	45
Max. products per 16A B Breaker	27
Connectable conductor cross section - Max (mm ²)	2.5

LIFETIME DATA

Lifespan L80 B20	50000
------------------	-------

PHYSICAL DATA

NILO 1200 DIR/INDIR 3K DALI WHITE 2050608

Housing colour	White
IP rating	IP20
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PMMA Acrylic
Nominal Product Height (mm)	65
Nominal Product Diameter (mm)	1140
Weight (kg)	8.2

PACKAGING

Product EAN number	5025768506088
Packaging single length / height (cm)	126.0
Packaging single width (cm)	126.0
Packaging single depth (cm)	14.9
DUN14 (inner)	05025768506088
Units per outer package	1
Packaging outer length / height (cm)	126.0
Packaging outer width (cm)	126.0
Packaging outer depth (cm)	14.9

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	1-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No