



Features

- Experience enchanting Flexible Filament LED lamps, blending timeless charm with cutting-edge technology - say goodbye to ordinary LED filament lamps! Sylvania ToLEDo™ Vintage lamps boast superior design, higher lumen output, making them perfect for general illumination, creating cosy ambience and decorative lighting. Illuminate your living rooms, dining areas, and kitchens at home with elegance or create a captivating ambience in hotels, restaurants, bars, and heritage spaces Lumen output -250lm 15,000 hours average rated life -last 7.5 times longer than incandescent vintage lamps Replace up to 25W incandescent lamps with ease, while enjoying dimmable lighting with approved dimmers. Environment friendly – no mercury and lower CO2 emissions Backed by a 3-year warranty for complete peace of mind.


Product Overview

Product name	ToLEDo Vintage Candle DIM 250LM E14 SL
Technology	LED
Lamp shape	Candle
Cap/Base	E14
Lamp finish	Other
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Correlated colour temperature (k)	2000
Light colour	Candlelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	330
Photobiological Risk Group	RG1
Wattage (W)	3.5

ToLEDo Vintage Candle DIM 250LM E14 SL
0030150

Power consumption (W)	3.5
Dimmable	Yes
IP rating	IP20
Product EAN number	5410288301501
Warranty	3 years
Useful luminous flux (#use)	250

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo Vintage Candle DIM 250LM E14 SL
Technology	LED
Lamp shape	Candle
Cap/Base	E14
Lamp finish	Other
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001959
Warranty	3 years



ToLEDo Vintage Candle DIM 250LM E14 SL
0030150

OPTICAL DATA

Useful luminous flux (#use)	250
Correlated colour temperature (k)	2000
Light colour	Candlelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	330
Photobiological Risk Group	RG1

ELECTRICAL DATA

Power consumption (W)	3.5
Wattage (W)	3.5
Equivalent watt (W)	25
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
Dimmable	Yes
Inrush Current (A)	0.26
Inrush Duration (µs)	330
Lamp Energy Label (class)	G
Nominal Frequency (Hz)	50/60Hz

LIFETIME DATA

Lifespan L70 B50	15000
------------------	-------

PHYSICAL DATA

IP rating	IP20
Nominal Product Height (mm)	92
Nominal Product Diameter (mm)	35
Weight (kg)	0.014

PACKAGING




ToLEDo Vintage Candle DIM 250LM E14 SL
0030150

Product EAN number	5410288301501
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	11.0
DUN14 (inner)	15410288301508
Units per outer package	6
Packaging outer length / height (cm)	14.3
Packaging outer width (cm)	9.7
Packaging outer depth (cm)	12.0


SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	Yes
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

Energy label



4
kWh/1000h



4
kWh/1000h

