

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK 2059668



Features

• Integrated LED spotlight, black RAL 9005, compact and minimalist design, ideal for retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 55° wide beam, optics: Aluminium reflector, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 2208lm, luminaire efficacy: 105lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, trailing edge dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x190mm, weight: 0.96kg.


Product Overview

Product name	BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
ETIM Class	EC001744
E-number FI	4280818
E-number SE	7401245
Fixture luminous flux (lm)	2208
Luminaire efficacy (lm/W)	105

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK 2059668


LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	85
Colour Consistency (SDCM)	3
Beam Angle (°)	55
Photobiological Risk Group	RG1
Total power consumption (W)	21
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	3
Housing colour	Black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768596683
Warranty	5 years
Dimming method	Mains: trailing edge only

Photometry



BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK 2059668

Technical drawings



Data table

GENERAL DATA

Product name	BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4280818
E-number SE	7401245
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2208
Luminaire efficacy (lm/W)	105
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White

Concord

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK 2059668

CRI (Ra)	85
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	55
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	21
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	Mains: trailing edge only
Minimum dimming level (%)	3
Drive current (mA)	500
Inrush Current (A)	45
Inrush Duration (µs)	20
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	48
Max. products per 16A C Breaker	80

LIFETIME DATA

Lifespan L70 B50	72000
Lifespan L70 B10	72000
Lifespan L80 B50	72000
Lifespan L80 B20	72000
Lifespan L80 B10	72000
Lifespan L90 B50	43000
Lifespan L90 B20	36000

BEACON 85CRI 3K WIDE BEAM L3 TRAILING EDGE BLACK 2059668

Lifespan L90 B10	33000
------------------	-------

PHYSICAL DATA

Housing colour	Black
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	70
Nominal Product Width (mm)	130
Nominal Product Height (mm)	169
Weight (kg)	1.543

PACKAGING

Product EAN number	5025768596683
Packaging single length / height (cm)	6.299
Packaging single width (cm)	6.929
Packaging single depth (cm)	7.165
DUN14 (inner)	05025768596683
Units per outer package	1
Packaging outer length / height (cm)	6.299
Packaging outer width (cm)	6.929
Packaging outer depth (cm)	7.165

SAFETY DATA

Glow Wire Test (°C)	650
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No