


Start Flood IP65 10000LM 865 Black
0050173



Features

- The streamlined, durable, lightweight die-cast aluminium body makes Start Flood IP65 a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 10000 lm, 78 W, 128 lm/W, 6500K, non dimmable, CRI>80, IP65, IK07, Class I, lifespan L70:B50: 120000 hrs, 196 x 251 x 33 mm (L x W x H). Weight: 1.135 kg.


Product Overview

Product name	Start Flood IP65 10000LM 865 Black
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Wall surface mounted
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579635
Fixture luminous flux (lm)	10000
Luminaire efficacy (lm/W)	128
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	78
Electrical protection	Class I

Start Flood IP65 10000LM 865 Black
0050173


Control gear type	Not required
Dimmable	No
Housing colour	Black
IP rating	IP65
IK rating	IK07
Product EAN number	5410288501734
Warranty	3 years
Dimming method	N/A

Photometry



Start Flood IP65 10000LM 865 Black
0050173

Technical drawings



Data table

GENERAL DATA

Product name	Start Flood IP65 10000LM 865 Black
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Wall surface mounted
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
E-number FI	4579635
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	10000
Luminaire efficacy (lm/W)	128
Correlated colour temperature (k)	6500
Light colour	Cool White

Start Flood IP65 10000LM 865 Black 0050173

CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Distribution type	Symmetric
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	78
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	Not required
No. Of switching cycles before premature failures	>15000
Dimmable	No
Dimming method	N/A
Drive current (mA)	331
Inrush Current (A)	2
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	16
Max. products per 13A C Breaker	21
Max. products per 16A C Breaker	26
Max. products per 20A C Breaker	32
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	13
Max. products per 16A B Breaker	15
Max. products per 20A B Breaker	19

Start Flood IP65 10000LM 865 Black 0050173

Connectable conductor cross section - Min (mm ²)	1
--	---

Connectable conductor cross section - Max (mm ²)	1
--	---

LIFETIME DATA

Lifespan L70 B50	120000
------------------	--------

Lifespan L80 B50	105000
------------------	--------

Lifespan L80 B20	95000
------------------	-------

PHYSICAL DATA

Housing colour	Black
----------------	-------

IP rating	IP65
-----------	------

IK rating	IK07
-----------	------

Diffuser finish	Transparent
-----------------	-------------

Diffuser material	Glass
-------------------	-------

Reflector finish	Not Applicable
------------------	----------------

Nominal Product Length (mm)	196
-----------------------------	-----

Nominal Product Width (mm)	251
----------------------------	-----

Nominal Product Height (mm)	33
-----------------------------	----

Weight (kg)	1.135
-------------	-------

PACKAGING

Product EAN number	5410288501734
--------------------	---------------

Packaging single length / height (cm)	26.0
---------------------------------------	------

Packaging single width (cm)	5.0
-----------------------------	-----

Packaging single depth (cm)	22.5
-----------------------------	------

DUN14 (inner)	15410288501731
---------------	----------------

Units per outer package	6
-------------------------	---

Packaging outer length / height (cm)	53.5
--------------------------------------	------

Packaging outer width (cm)	17.0
----------------------------	------

Packaging outer depth (cm)	24.5
----------------------------	------

SAFETY DATA



Start Flood IP65 10000LM 865 Black
0050173

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No