



Features

- 5 metre IP20 LED reel with pre-attached 3M adhesive type; equipped with 600 LEDs; 5150lm per 5m (1030lm per 1m); 24V; 4000K; CRI90; R9>50; SDCM≤3;Compatible with emergency packs: 0046600, 0046601




Product Overview


Product name	Flex Pro IP20 5150lm 940
Technology	LED
General application	Hospitality
ETIM Class	EC002706
E-number FI	4278334
Fixture luminous flux (lm)	5150
Luminaire efficacy (lm/W)	107
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Photobiological Risk Group	RG1
Power consumption (W)	48
Total power consumption (W)	48
Electrical protection	Class III
Dimmable	Yes
IP rating	IP20
IK rating	IK00
Product EAN number	5410288681771
Warranty	5 years
Dimming method	Other

Flex Pro IP20 5150lm 940
0068177

Useful luminous flux (#use)	5150
Photometry	



Technical drawings



Data table

GENERAL DATA

Flex Pro IP20 5150lm 940 0068177

Product name	Flex Pro IP20 5150lm 940
Technology	LED
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
E-number FI	4278334
Warranty	5 years

OPTICAL DATA

Useful luminous flux (#use)	5150
Fixture luminous flux (lm)	5150
Luminaire efficacy (lm/W)	107
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Photobiological Risk Group	RG1

ELECTRICAL DATA

Power consumption (W)	48
Total power consumption (W)	48
Primary Supply/Product voltage - min (V)	24
Primary Supply/Product voltage - max (V)	24
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	2000
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	N/A

LIFETIME DATA

Lifespan L70 B50	54000
Lifespan L70 B10	54000
Lifespan L80 B10	50000
Lifespan L90 B10	44000

PHYSICAL DATA

IP rating	IP20
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	10
Nominal Product Height (mm)	1.2
Weight (kg)	0.2

PACKAGING

Product EAN number	5410288681771
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5
Packaging single depth (cm)	3.0
DUN14 (inner)	15410288681778
Units per outer package	20
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	24.0

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No

Energy label



0068177



48
kWh/1000h



2019/2015



0068177



48
kWh/1000h



2019/2015