



Features

- Integrated LED highbay; Black aluminium housing; 26400 Lm; 165 W; 160 Lm/W; 4000K; Drive current: 3200mA; CRI 80; 85° beam angle; Sylsmart SSA - Connected; IP65; Lifespan L80:B20 92,000 hrs; suspension wires included. Lampshades cannot be used for Granit SSA luminaires, as it disturbs the signal for the sensor.

Product Overview

Product name	Sylvania GRANIT IP65 26400LM 840 WB SSA
Technology	LED
Cap/Base	N/A
Mount	Ceiling surface mounting, Suspended
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	26400
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	165
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)

Housing colour	RAL9017
IP rating	IP65
IK rating	IK08
Product EAN number	5410288387710
Warranty	5 years
Dimming method	SylSmart SSA

Photometry

