

RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE
0052588



Features

• Ceiling Recessed LED Linear luminaire (lay-in), with Louvre + MPO diffuser, Direct Light Distribution, Luminaire Dimensions: 1196x296x52mm, Sylvania White body colour, IP20, IK07, Constant Current, Low LED flicker (+/-5%), Warm White (3000K), LED Colour Temperature, 3572lm, 30W, 119lm/W, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<18, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Glow Wire Test 850°C, Quick and easy electrical connection with direct access to push-connectors on top, 2 x metallic safety cables (1.5m) included, the luminaire can be covered with building insulation of Glass Wool type.


Product Overview

Product name	RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3572
Luminous flux (lm)	3572
Luminaire efficacy (lm/W)	119
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 18
Photobiological Risk Group	RG0
Total power consumption (W)	30

RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE
0052588

Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5410288525884
Warranty	5 years
Dimming method	N/A
Useful luminous flux (#use)	3572

Photometry



Technical drawings

