


Adapting Ring RAL9010 225/255-270/280 **0030464**





Features

• Adapting ring is suitable for the fixture of 225mm cut out. When put together, it can be used in a new cut out of 255mm- max 270mm. Outer ring of 280mm dia. RAL9010.


Product Overview

| Product name | Adapting Ring RAL9010 225/255-270/280 |
|---------------------|--|
| Technology | Accessory |
| Mount | Ceiling recessed mounting |
| General application | Education, Hospitality, Office, Retail |
| ETIM Class | EC002557 |
| E-number FI | 4278415 |
| Housing colour | RAL9010 |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5410288304649 |
| Warranty | 3 years |



Adapting Ring RAL9010 225/255-270/280 **0030464**

Technical drawings



Data table

GENERAL DATA

| Product name | Adapting Ring RAL9010 225/255-270/280 |
|---------------------|--|
| Technology | Accessory |
| Type of accessory | Other |
| Mount | Ceiling recessed mounting |
| General application | Education, Hospitality, Office, Retail |
| ETIM Class | EC002557 |
| E-number FI | 4278415 |
| Warranty | 3 years |

ELECTRICAL DATA

Control gear required No

PHYSICAL DATA

| Housing colour | RAL9010 |
|----------------|---------|
| IP rating | IP20 |



Adapting Ring RAL9010 225/255-270/280 **0030464**

| IK rating | IK02 |
|-------------|-------|
| Weight (kg) | 0.374 |

PACKAGING

| Product EAN number | 5410288304649 |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 29.7 |
| Packaging single width (cm) | 4.5 |
| Packaging single depth (cm) | 29.2 |
| DUN14 (inner) | 15410288304646 |
| Units per outer package | 20 |
| Packaging outer length / height (cm) | 61.0 |
| Packaging outer width (cm) | 24.5 |
| Packaging outer depth (cm) | 60.5 |

SAFETY DATA

| Special purpose lamp | No |
|-------------------------------------|----|
| Dry applications use only | No |
| Suitable for household illumination | No |