


GIOTTO 305 4000K SURFACE MW SENSOR  
3034776



Features

- Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1750lm, 16.5W, 107lm/W, 4000K, CRI 80, non-dimmable, integral microwave sensor. 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.


Product Overview

|                                   |                                                 |
|-----------------------------------|-------------------------------------------------|
| Product name                      | GIOTTO 305 4000K SURFACE MW SENSOR              |
| Technology                        | LED                                             |
| Cap/Base                          | N/A                                             |
| Housing                           | PC Polycarbonate                                |
| Mount                             | Ceiling recessed mounting, Wall surface mounted |
| Environment                       | Indoor                                          |
| General application               | Hospitality, Logistics & Industry               |
| ETIM Class                        | EC002892                                        |
| E-number FI                       | 4225705                                         |
| Fixture luminous flux (lm)        | 1750                                            |
| Luminaire efficacy (lm/W)         | 107                                             |
| Correlated colour temperature (k) | 4000                                            |
| Light colour                      | Neutral White                                   |
| CRI (Ra)                          | 80                                              |
| Colour Variation Initial (SDCM)   | 3                                               |
| Beam Angle (°)                    | 120                                             |
| Glare control                     | < 25                                            |
| Photobiological Risk Group        | RG0                                             |
| Total power consumption (W)       | 16.5                                            |

GIOTTO 305 4000K SURFACE MW SENSOR  
3034776

|                       |                             |
|-----------------------|-----------------------------|
| Electrical protection | Class I                     |
| Control gear type     | LED driver constant current |
| Control gear mounting | Integrated                  |
| Dimmable              | No                          |
| LED Flickering Rate   | Ultra low (5% or less)      |
| Housing colour        | White                       |
| IP rating             | IP44                        |
| IK rating             | IK10                        |
| Product EAN number    | 8711971347767               |
| Warranty              | 5 years                     |
| Dimming method        | N/A                         |
| Colour Code           | 840                         |


Photometry



GIOTTO 305 4000K SURFACE MW SENSOR  
3034776

Technical drawings

Giotto 305 surface mounted



Data table

GENERAL DATA

|                                         |                                                 |
|-----------------------------------------|-------------------------------------------------|
| Product name                            | GIOTTO 305 4000K SURFACE MW SENSOR              |
| Technology                              | LED                                             |
| Cap/Base                                | N/A                                             |
| Housing                                 | PC Polycarbonate                                |
| Mount                                   | Ceiling recessed mounting, Wall surface mounted |
| Environment                             | Indoor                                          |
| General application                     | Hospitality, Logistics & Industry               |
| Operating temperature range (°C)        | -25°C...+25°C                                   |
| Performance ambient temperature Tq (°C) | 25                                              |
| ETIM Class                              | EC002892                                        |
| E-number FI                             | 4225705                                         |
| Warranty                                | 5 years                                         |

OPTICAL DATA

|                                   |               |
|-----------------------------------|---------------|
| Fixture luminous flux (lm)        | 1750          |
| Luminaire efficacy (lm/W)         | 107           |
| Correlated colour temperature (k) | 4000          |
| Colour Code                       | 840           |
| Light colour                      | Neutral White |

## GIOTTO 305 4000K SURFACE MW SENSOR 3034776

|                                              |           |
|----------------------------------------------|-----------|
| CRI (Ra)                                     | 80        |
| Colour Variation Initial (SDCM)              | 3         |
| Adjustable chromaticity                      | N         |
| Beam Angle (°)                               | 120       |
| Distribution type                            | Symmetric |
| Glare control                                | < 25      |
| Photobiological Risk Group                   | RG0       |
| Lumen maintenance at end of nominal life (%) | 80        |

### ELECTRICAL DATA

|                                                          |                             |
|----------------------------------------------------------|-----------------------------|
| Total power consumption (W)                              | 16.5                        |
| Primary Supply/Product voltage - min (V)                 | 220                         |
| Primary Supply/Product voltage - max (V)                 | 240                         |
| Lamp power factor                                        | 0.95                        |
| Electrical protection                                    | Class I                     |
| Control gear required                                    | No                          |
| Control gear type                                        | LED driver constant current |
| Control gear mounting                                    | Integrated                  |
| Dimmable                                                 | No                          |
| Dimming method                                           | N/A                         |
| Drive current (mA)                                       | 600                         |
| Inrush Current (A)                                       | 40                          |
| Inrush Duration (µs)                                     | 400                         |
| Energy Efficiency Class (A->G) of contained light source | D                           |
| Nominal Frequency (Hz)                                   | 50/60Hz                     |
| LED Flickering Rate                                      | Ultra low (5% or less)      |
| Max. products per 10A C Breaker                          | 52                          |
| Max. products per 16A C Breaker                          | 85                          |
| Max. products per 20A C Breaker                          | 104                         |
| Max. products per 10A B Breaker                          | 31                          |
| Max. products per 16A B Breaker                          | 50                          |
| Max. products per 20A B Breaker                          | 62                          |



GIOTTO 305 4000K SURFACE MW SENSOR  
3034776

|                                                 |      |
|-------------------------------------------------|------|
| Connectable conductor cross section - Min (mm²) | 0.75 |
| Connectable conductor cross section - Max (mm²) | 2.5  |

LIFETIME DATA

|                  |        |
|------------------|--------|
| Lifespan L70 B10 | 120000 |
| Lifespan L80 B50 | 120000 |
| Lifespan L90 B50 | 74500  |

PHYSICAL DATA

|                               |                  |
|-------------------------------|------------------|
| Housing colour                | White            |
| IP rating                     | IP44             |
| IK rating                     | IK10             |
| Diffuser finish               | Opal             |
| Diffuser material             | PC Polycarbonate |
| Nominal Product Height (mm)   | 104              |
| Nominal Product Diameter (mm) | 305              |
| Weight (kg)                   | 1.11             |

PACKAGING

|                                       |                |
|---------------------------------------|----------------|
| Product EAN number                    | 8711971347767  |
| Packaging single length / height (cm) | 32.5           |
| Packaging single width (cm)           | 32.5           |
| Packaging single depth (cm)           | 10.0           |
| DUN14 (inner)                         | 08711971347767 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 32.5           |
| Packaging outer width (cm)            | 32.5           |
| Packaging outer depth (cm)            | 10.0           |

SAFETY DATA

|                     |     |
|---------------------|-----|
| Glow Wire Test (°C) | 850 |
|---------------------|-----|



GIOTTO 305 4000K SURFACE MW SENSOR  
3034776

|                                     |        |
|-------------------------------------|--------|
| Optimal operating condition (°C)    | -25-25 |
| Special purpose lamp                | No     |
| Dry applications use only           | No     |
| Suitable for household illumination | No     |