

## ToLEDo Platinum RT Candle 485LM 840 E14 SL 0030139















• Ultra-efficient LED filament lamp range with the same reminiscent look of the classic traditional lampSave up to 95% on energy bills compared to old incandescent lampsEnergy Class A and best-in-class lumen efficacySustainable and eco-friendly solutionLast three times longer than the standard LED retrofit lampsRemarkable 50,000 hours average rated life – reducing the hassle of frequent replacementsSparkling light effectIdeal for everyday lighting in homes, hotels, restaurants and moreOmni-directional light distributionNon-dimmable

## **Product Overview**

| Product name                      | ToLEDo Platinum RT Candle 485LM 840 E14 SL |
|-----------------------------------|--|
| Technology                        | LED  |
| Lamp shape                        | Candle                                     |
| Cap/Base                          | E14  |
| Lamp finish                       | Clear                                      |
| Fixture rating                    | Open                                       |
| General application               | Hospitality, Residential & Consumer        |
| ETIM Class                        | EC001959                                   |
| E-number FI                       | 4741178                                    |
| Correlated colour temperature (k) | 4000                                       |
| Light colour                      | Cool White                                 |
| CRI (Ra)                          | 80   |
| Colour Variation Initial (SDCM)   | 6  |
| Beam Angle (°)                    | 320  |
| Photobiological Risk Group        | RG1  |
| Wattage (W)                       | 2.3  |
| Power consumption (W)             | 2.2  |
| Control gear type                 | LED driver constant current                |



## ToLEDo Platinum RT Candle 485LM 840 E14 SL **0030139**

| Dimmable                    | No            |
|-----------------------------|---------------|
| Housing colour              | Transparent   |
| IP rating                   | IP20          |
| Product EAN number          | 5410288301396 |
| Warranty                    | 5 years       |
| Dimming method              | N/A           |
| Useful luminous flux (#use) | 485           |

## **Technical drawings**

