



Features

- Exterior LED Floodlight, comes complete with 1000mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, integrated anti-condensation valve, IP66, IK08, Class I, 4000K, CRI80, Non-dimmable, 7300lm, 51W, 143lm/W, Asymmetrical Wide beam, 100.000hrs L80B50 lifespan, 331 x 237 x 68mm (LxWxD) dimensions, 2.3kg weight, RAL9017 Traffic Black color, Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3.


Product Overview

|                                   |                             |
|-----------------------------------|-----------------------------|
| Product name                      | Kalani IP66 7KLM 840 ASYM   |
| Technology                        | LED                         |
| Cap/Base                          | N/A                         |
| Housing                           | Aluminium                   |
| Mount                             | Other                       |
| General application               | Logistics & Industry        |
| ETIM Class                        | EC001744                    |
| E-number FI                       | 4579616                     |
| Fixture luminous flux (lm)        | 7300                        |
| Luminaire efficacy (lm/W)         | 143                         |
| Correlated colour temperature (k) | 4000                        |
| Light colour                      | Neutral White               |
| CRI (Ra)                          | 80                          |
| Colour Variation Initial (SDCM)   | 3                           |
| Beam Angle (°)                    | 65x120                      |
| Photobiological Risk Group        | RG1                         |
| Total power consumption (W)       | 51                          |
| Electrical protection             | Class I                     |
| Control gear type                 | LED driver constant current |

Kalani IP66 7KLM 840 ASYM  
**0056711**


|                     |                |
|---------------------|----------------|
| Dimmable            | No             |
| LED Flickering Rate | Low (6% - 20%) |
| Housing colour      | RAL9017        |
| IP rating           | IP66           |
| IK rating           | IK08           |
| Product EAN number  | 5410288567112  |
| Warranty            | 5 years        |
| Dimming method      | N/A            |

**Photometry**



Kalani IP66 7KLM 840 ASYM  
0056711

Technical drawings



Data table

GENERAL DATA

|                                  |                           |
|----------------------------------|---------------------------|
| Product name                     | Kalani IP66 7KLM 840 ASYM |
| Technology                       | LED                       |
| Cap/Base                         | N/A                       |
| Housing                          | Aluminium                 |
| Mount                            | Other                     |
| General application              | Logistics & Industry      |
| Operating temperature range (°C) | -30°C...+50°C             |
| ETIM Class                       | EC001744                  |
| E-number FI                      | 4579616                   |
| Warranty                         | 5 years                   |

OPTICAL DATA

|                                   |               |
|-----------------------------------|---------------|
| Fixture luminous flux (lm)        | 7300          |
| Luminaire efficacy (lm/W)         | 143           |
| Correlated colour temperature (k) | 4000          |
| Light colour                      | Neutral White |

## Kalani IP66 7KLM 840 ASYM 0056711

|                                 |            |
|---------------------------------|------------|
| CRI (Ra)                        | 80         |
| Colour Variation Initial (SDCM) | 3          |
| Beam Angle (°)                  | 65x120     |
| Distribution type               | Asymmetric |
| Photobiological Risk Group      | RG1        |

### ELECTRICAL DATA

|                                                                  |                             |
|------------------------------------------------------------------|-----------------------------|
| Total power consumption (W)                                      | 51                          |
| Primary Supply/Product voltage - min (V)                         | 220.0                       |
| Primary Supply/Product voltage - max (V)                         | 240.0                       |
| Lamp power factor                                                | 0.95                        |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 20                          |
| Electrical protection                                            | Class I                     |
| Control gear required                                            | No                          |
| Control gear type                                                | LED driver constant current |
| Dimmable                                                         | No                          |
| Dimming method                                                   | N/A                         |
| Drive current (mA)                                               | 220                         |
| Inrush Current (A)                                               | 60                          |
| Inrush Duration (µs)                                             | 350                         |
| Energy Efficiency Class (A->G) of contained light source         | D                           |
| Nominal Frequency (Hz)                                           | 50/60Hz                     |
| LED Flickering Rate                                              | Low (6% - 20%)              |
| Max. products per 10A C Breaker                                  | 14                          |
| Max. products per 13A C Breaker                                  | 18                          |
| Max. products per 16A C Breaker                                  | 22                          |
| Max. products per 20A C Breaker                                  | 28                          |
| Max. products per 10A B Breaker                                  | 11                          |
| Max. products per 13A B Breaker                                  | 14                          |
| Max. products per 16A B Breaker                                  | 19                          |
| Max. products per 20A B Breaker                                  | 22                          |
| Mains surge immunity (differential mode -> L-N) (kV)             | 10                          |

## Kalani IP66 7KLM 840 ASYM 0056711

|                                                              |    |
|--------------------------------------------------------------|----|
| Mains surge immunity (common mode -> L/N - GND) (kV)         | 10 |
| Connectable conductor cross section - Min (mm <sup>2</sup> ) | 1  |
| Connectable conductor cross section - Max (mm <sup>2</sup> ) | 1  |

### LIFETIME DATA

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 100000 |
| Lifespan L80 B20 | 91000  |

### PHYSICAL DATA

|                             |             |
|-----------------------------|-------------|
| Housing colour              | RAL9017     |
| IP rating                   | IP66        |
| IK rating                   | IK08        |
| Diffuser finish             | Transparent |
| Diffuser material           | Glass       |
| Reflector finish            | Matt        |
| Nominal Product Length (mm) | 331         |
| Nominal Product Width (mm)  | 237         |
| Nominal Product Height (mm) | 68          |
| Weight (kg)                 | 2.3         |

### PACKAGING

|                                       |                |
|---------------------------------------|----------------|
| Product EAN number                    | 5410288567112  |
| Packaging single length / height (cm) | 24.8           |
| Packaging single width (cm)           | 8.1            |
| Packaging single depth (cm)           | 34.5           |
| DUN14 (inner)                         | 05410288567112 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 24.8           |
| Packaging outer width (cm)            | 8.1            |
| Packaging outer depth (cm)            | 34.5           |



Kalani IP66 7KLM 840 ASYM  
0056711

SAFETY DATA

|                                     |        |
|-------------------------------------|--------|
| Glow Wire Test (°C)                 | 650    |
| Optimal operating condition (°C)    | -30-50 |
| Special purpose lamp                | No     |
| Dry applications use only           | No     |
| Suitable for household illumination | No     |