

OTAO LINEAR OPAL ROLLED DIFF 30M  
0041821



Features

- Clip-in opal diffuser to build seamless continuous line for Otao Linear with opal diffuser, 30m length.

Product Overview

|                                 |                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------|
| Product name                    | OTAO LINEAR OPAL ROLLED DIFF 30M                                                     |
| Technology                      | LED (3 SDCM)                                                                         |
| Housing                         | PC Polycarbonate                                                                     |
| Mount                           | Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended |
| General application             | Office, Education                                                                    |
| ETIM Class                      | EC002557                                                                             |
| E-number FI                     | 4170607                                                                              |
| Colour Variation Initial (SDCM) | N/A                                                                                  |
| Photobiological Risk Group      | Not applicable                                                                       |
| Housing colour                  | White                                                                                |
| IP rating                       | IP20                                                                                 |
| IK rating                       | IK03                                                                                 |
| Product EAN number              | 5410288418216                                                                        |
| Warranty                        | 5 years                                                                              |

Data table

GENERAL DATA

|                   |                                  |
|-------------------|----------------------------------|
| Product name      | OTAO LINEAR OPAL ROLLED DIFF 30M |
| Technology        | LED (3 SDCM)                     |
| Type of accessory | Optical accessory                |

## OTAO LINEAR OPAL ROLLED DIFF 30M 0041821

|                                         |                                                                                      |
|-----------------------------------------|--------------------------------------------------------------------------------------|
| <b>Housing</b>                          | PC Polycarbonate                                                                     |
| <b>Mount</b>                            | Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended |
| <b>General application</b>              | Office, Education                                                                    |
| <b>Operating temperature range (°C)</b> | 5°C...+50°C                                                                          |
| <b>ETIM Class</b>                       | EC002557                                                                             |
| <b>E-number FI</b>                      | 4170607                                                                              |
| <b>Warranty</b>                         | 5 years                                                                              |

### OPTICAL DATA

|                                        |                |
|----------------------------------------|----------------|
| <b>Colour Variation Initial (SDCM)</b> | N/A            |
| <b>Photobiological Risk Group</b>      | Not applicable |

### ELECTRICAL DATA

|                              |    |
|------------------------------|----|
| <b>Control gear required</b> | No |
|------------------------------|----|

### PHYSICAL DATA

|                       |       |
|-----------------------|-------|
| <b>Housing colour</b> | White |
| <b>IP rating</b>      | IP20  |
| <b>IK rating</b>      | IK03  |
| <b>Weight (kg)</b>    | 1.75  |

### PACKAGING

|                                              |                |
|----------------------------------------------|----------------|
| <b>Product EAN number</b>                    | 5410288418216  |
| <b>Packaging single length / height (cm)</b> | 55.0           |
| <b>Packaging single width (cm)</b>           | 5.5            |
| <b>Packaging single depth (cm)</b>           | 55.0           |
| <b>DUN14 (inner)</b>                         | 15410288418213 |
| <b>Units per outer package</b>               | 5              |
| <b>Packaging outer length / height (cm)</b>  | 57.0           |
| <b>Packaging outer width (cm)</b>            | 32.0           |
| <b>Packaging outer depth (cm)</b>            | 57.0           |



OTAO LINEAR OPAL ROLLED DIFF 30M  
0041821

SAFETY DATA

|                                     |      |
|-------------------------------------|------|
| Glow Wire Test (°C)                 | 650  |
| Optimal operating condition (°C)    | 5-50 |
| Special purpose lamp                | No   |
| Dry applications use only           | No   |
| Suitable for household illumination | No   |