


Start Flood Flat IP65 2000LM 840 Black
0050110



Features

• The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 2000 lm, 18 W, 111 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 110 x 123 x 26 mm (L x W x H). Weight: 0.39kg.


Product Overview

Product name	Start Flood Flat IP65 2000LM 840 Black
Technology	LED
Cap/Base	N/A
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579529
Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	111
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	18
Electrical protection	Class I
Dimmable	No
LED Flickering Rate	Low (6% - 20%)


Start Flood Flat IP65 2000LM 840 Black
0050110

Housing colour	Black
IP rating	IP65
IK rating	IK06
Product EAN number	5410288501109
Warranty	3 years
Dimming method	N/A

Photometry



Technical drawings



Start Flood Flat IP65 2000LM 840 Black
0050110

Data table

GENERAL DATA

Product name	Start Flood Flat IP65 2000LM 840 Black
Technology	LED
Cap/Base	N/A
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
E-number FI	4579529
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	111
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	18
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class I
Control gear required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	38
Inrush Current (A)	19.4

Start Flood Flat IP65 2000LM 840 Black 0050110

Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	16
Max. products per 13A C Breaker	21
Max. products per 16A C Breaker	26
Max. products per 20A C Breaker	32
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	12
Max. products per 16A B Breaker	15
Max. products per 20A B Breaker	19

LIFETIME DATA

Lifespan L70 B50	90000
Lifespan L80 B50	85000
Lifespan L80 B20	54000

PHYSICAL DATA

Housing colour	Black
IP rating	IP65
IK rating	IK06
Nominal Product Length (mm)	110
Nominal Product Width (mm)	123
Nominal Product Height (mm)	26
Weight (kg)	0.32

PACKAGING

Product EAN number	5410288501109
Packaging single length / height (cm)	13.0
Packaging single width (cm)	5.5
Packaging single depth (cm)	15.5
DUN14 (inner)	15410288501106



Start Flood Flat IP65 2000LM 840 Black
0050110

Units per outer package	6
Packaging outer length / height (cm)	36.0
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	17.5

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No