


Start Flood Flat IP65 950LM 830 Black
0050105



Features

- The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 950 lm, 9 W, 106 lm/W, 3000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 100 x 105 x 23 mm (L x W x H). Weight: 0.32kg.


Product Overview

Product name	Start Flood Flat IP65 950LM 830 Black
Technology	LED
Cap/Base	N/A
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579526
Fixture luminous flux (lm)	950
Luminaire efficacy (lm/W)	106
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class I
LED Flickering Rate	Low (6% - 20%)
Housing colour	Black

Start Flood Flat IP65 950LM 830 Black
0050105

IP rating	IP65
IK rating	IK06
Product EAN number	5410288501055
Warranty	3 years
Dimming method	N/A
Useful luminous flux (#use)	950

Photometry



Technical drawings

