



Features

- Integrated LED recessed spotlight, vertical tilt 30°, black aluminium bezel finish, dimmable trailing/leading edge, 3-CCT changeable 2700-3000-4000K, 50° degree beam angle, polycarbonate and aluminium body, low profile 62mm recessed depth, IP44 from the front, IK07, loop-in/loop-out terminals for fast wiring, 68mm cutout, clear lens. Additional white or gold reflectors can be ordered as accessory.


Product Overview

Product name	START SPOT ALU 760LM 3CCT DIM IP44 BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4279309
Fixture luminous flux (lm)	760
Luminaire efficacy (lm/W)	87
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	50
Photobiological Risk Group	RG1
Total power consumption (W)	8.7
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	RAL9005
IP rating	IP44/20

START SPOT ALU 760LM 3CCT DIM IP44 BLK 0005186

IK rating	IK07
Product EAN number	5410288051864
Warranty	5 years
Dimming method	Mains: leading / trailing edge
Useful luminous flux (#use)	760

Photometry



Technical drawings

