

SylWork Flood 2000LM 840 IP65 0090004














Features

• • Slim LED portable work light • Lightweight, slim, stylish robust, high-quality plastic body • Stable, flexible positioning with stand or Tripod • Housing material: PC housing, glass lens and metal bracket • Option to use 2 work lights in the same time installed on the same Tripod • Mains operated version • Space-saving design - Tripod version can be folded up and stowed away • 4000K Cool White light • Total system efficacy up to 100lm/W • CRI >80 • Operating temperature range: -20 to +40°C • Lifetime: 30.000 hrs (L70/B50) • 3 year warranty

Product Overview

| Product name | SylWork Flood 2000LM 840 IP65 |
|-----------------------------------|-------------------------------|
| Technology | LED |
| Cap/Base | N/A |
| Housing | Metal/plastic |
| General application | Residential & Consumer |
| ETIM Class | EC000346 |
| E-number FI | 4357146 |
| Fixture luminous flux (lm) | 2000 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 20 |
| Electrical protection | Class I |
| IP rating | IP65 |
| IK rating | IK07 |
| Product EAN number | 5410288900049 |
| Warranty | 3 years |
| Dimming method | Onboard pot |



SylWork Flood 2000LM 840 IP65 **0090004**

Technical drawings

