



Features

- Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp
- Modern construction and attractive design
- Mercury free solution
- Long average rated lifetime: 15,000 hours
- Lower maintenance cost compared to traditional lamps
- Non-dimmable
- 3 years warranty
- Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc



Product Overview

Product name	RefLED R39 V4 250LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	2.9
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Photobiological Risk Group	RG1
Wattage (W)	2.9
Power consumption (W)	2.9
Dimmable	No
Average life (Nominal) (h)	15000

RefLED R39 V4 250LM 865 E14 SL
0029204

Product EAN number	5410288292045
Warranty	3 years
Useful luminous flux (#use)	250

Technical drawings



Data table

GENERAL DATA

Product name	RefLED R39 V4 250LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	2.9
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959



RefLED R39 V4 250LM 865 E14 SL
0029204

Warranty	3 years
----------	---------

OPTICAL DATA

Useful luminous flux (#use)	250
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	2.9
Wattage (W)	2.9
Equivalent watt (W)	25
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	1.2
Inrush Duration (µs)	150
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	133
Max. products per 16A B Breaker	67

LIFETIME DATA

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000



RefLED R39 V4 250LM 865 E14 SL
0029204

Average life (Rated) (h)	15000
--------------------------	-------

PHYSICAL DATA

Nominal Product Length (mm)	67
Nominal Product Diameter (mm)	39
Weight (kg)	0.055


PACKAGING

Product EAN number	5410288292045
Packaging single length / height (cm)	8.35
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
DUN14 (inner)	15410288292042
Units per outer package	6
Packaging outer length / height (cm)	15.8
Packaging outer width (cm)	10.7
Packaging outer depth (cm)	9.1

SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures


Energy label



3
kWh/1000h



2019/2015



3
kWh/1000h



2019/2015