

Concord

OFFICELYTE 600 3000K HE

2069512



Features

• Concord OFFICELYTE 600 3000K HE is a high performance low glare luminaire for offices and education applications. Suitable for lay in, as well as for pull up, into concealed grid and plasterboard ceilings with our optional wedge accessory kits suitable. Optical solution is a combination of Tp(a) rated central prismatic and side diffusers. Painted steel housing with RAL 9016 finishing colour. 595x595x92mm dimensions. 3150lm luminous flux, 23.5W total power consumption, 134lm/W efficacy level, CRI80 3000K (Warm white) LED light sources with chromaticity tolerance of 3-step MacAdam ellipse. Conforming to EN 12464-1 for indoor work places, UGR<19. IK03 impact resistance, IP20 ingress protection level. IEC Class II electrical protection. Photobiological Risk Group 0. Lifespan 93k hours at L80B50. Glow Wire test 850°C. Non-dimmable driver.


Product Overview

Product name	OFFICELYTE 600 3000K HE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Office, Education
ETIM Class	EC002892
Fixture luminous flux (lm)	3150
Luminaire efficacy (lm/W)	134
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3

OFFICELYTE 600 3000K HE 2069512

Beam Angle (°)	87
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	23.5
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Housing colour	RAL9016
IP rating	IP20
IK rating	IK03
Product EAN number	5025768695126
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

