

Features

- Logistics and Industry high bay luminaire with Symmetrical Wide beam optics to provide homogenous light distribution for open space areas, comes complete with 2000mm flying lead and 1000mm suspension cable, aluminium housing, PC diffuser, IP65, IK08, Class I, 4000K, CRI80, 3 step MacAdam ellipse, DALI dimmable, 26500lm, 142W, 187lm/W, 105.000hrs L80B50 lifespan, 446 x 481 x 86mm (LxWxD) dimensions, 4.68kg weight, RAL7012 Basalt Grey color, -30...+50°C operating temperature range.


Product Overview

Product name	Rocks IP65 26KLM 840 WIDE DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4327131
Fixture luminous flux (lm)	26500
Luminaire efficacy (lm/W)	187
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	75
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	142

Rocks IP65 26KLM 840 WIDE DALI
2825406

Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5025768254064
Warranty	5 years
Dimming method	DALI-2

Photometry



Technical drawings

