




Features

- SylSafe Bay MB C EM3 NM MS is a dust and waterproof surface mounted emergency luminaire for industrial applications. Midbay optics for medium ceiling heights. Non-maintained 3hr emergency duration with NiMH rechargeable battery. Recharge period 24 hours. 200lm, 3W, IK03, IP65. Power Factor 0.44. Class II electrical construction.


Product Overview

Product name	SylSafe Bay MB C EM3 NM MS
Technology	LED
Mount	Ceiling surface mounting
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry
ETIM Class	EC001957
Fixture luminous flux (lm)	200
Luminaire efficacy (lm/W)	67
Correlated colour temperature (k)	5700
CRI (Ra)	75
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	200
Electrical protection	Class II
Housing colour	White
IP rating	IP65
IK rating	IK03
Product EAN number	5410288417356
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name SylSafe Bay MB C EM3 NM MS

SylSafe Bay MB C EM3 NM MS 0041735

Technology	LED
Mount	Ceiling surface mounting
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry
ETIM Class	EC001957
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	200
Luminaire efficacy (lm/W)	67
Correlated colour temperature (k)	5700
CRI (Ra)	75
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	200
Emergency duration (h)	3

ELECTRICAL DATA

Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.44
Electrical protection	Class II
Control gear required	Yes
Drive current (mA)	30
Nominal Frequency (Hz)	50/60Hz

PHYSICAL DATA

Housing colour	White
IP rating	IP65
IK rating	IK03
Nominal Product Length (mm)	197
Nominal Product Width (mm)	197
Nominal Product Height (mm)	53
Weight (kg)	0.588



SylSafe Bay MB C EM3 NM MS
0041735

PACKAGING

Product EAN number	5410288417356
Packaging single length / height (cm)	23.0
Packaging single width (cm)	15.0
Packaging single depth (cm)	7.0
DUN14 (inner)	05410288417356
Units per outer package	5
Packaging outer length / height (cm)	42.2
Packaging outer width (cm)	25.2
Packaging outer depth (cm)	13.2

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No