


Insaver Slim UGR19 175 IP54 PIR 1075lm 840
0030321



Features

• Insaver Slim is a ceiling recessed LED downlight (IP54 from the front),with integrated PIR sensor with time (up to 8 mins) and daylight lux level settings. Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 9W; 1075lm; 119lm/W; 4000K; UGR <19 with shallow product depth 50mm. Meets TP(a) requirements.


Product Overview

Product name	Insaver Slim UGR19 175 IP54 PIR 1075lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4276932
Fixture luminous flux (lm)	1075
Luminaire efficacy (lm/W)	119
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class II
Control gear type	LED driver constant current

Insaver Slim UGR19 175 IP54 PIR 1075lm 840
0030321


Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9003
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303215
Warranty	5 years

Photometry



Insaver Slim UGR19 175 IP54 PIR 1075lm 840
0030321

Technical drawings



Data table

GENERAL DATA

Product name	Insaver Slim UGR19 175 IP54 PIR 1075lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	40
ETIM Class	EC001744
E-number FI	4276932
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	1075
Luminaire efficacy (lm/W)	119

Insaver Slim UGR19 175 IP54 PIR 1075lm 840 0030321

Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	9
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20.0
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
No. Of switching cycles before premature failures	>100000
Dimmable	No
Drive current (mA)	290
Inrush Current (A)	7.48
Inrush Duration (µs)	160
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	56
Max. products per 13A C Breaker	70
Max. products per 16A C Breaker	88
Max. products per 20A C Breaker	110
Max. products per 10A B Breaker	33
Max. products per 13A B Breaker	42

Insaver Slim UGR19 175 IP54 PIR 1075lm 840 0030321

Max. products per 16A B Breaker	52
Max. products per 20A B Breaker	66
Connectable conductor cross section - Min (mm ²)	0.26
Connectable conductor cross section - Max (mm ²)	1.26

LIFETIME DATA

Lifespan L70 B50	90000
Lifespan L80 B20	90000
Lifespan L90 B10	39000

PHYSICAL DATA

Housing colour	RAL9003
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Reflector finish	Not Applicable
Nominal Product Height (mm)	50
Nominal Product Diameter (mm)	195
Built-in diameter (mm)	175
Weight (kg)	0.913
Recessed Depth (mm)	150

PACKAGING

Product EAN number	5410288303215
Packaging single length / height (cm)	25.5
Packaging single width (cm)	25.5
Packaging single depth (cm)	8.5
DUN14 (inner)	15410288303212
Units per outer package	12
Packaging outer length / height (cm)	52.5
Packaging outer width (cm)	52.5



Insaver Slim UGR19 175 IP54 PIR 1075lm 840
0030321

Packaging outer depth (cm)	27.5
----------------------------	------

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-10-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No