## Concord


### BEACON ACCENT 97CRI 4K MEDIUM BEAM L3 ON-BOARD DIM WHITE 2059565















#### **Features**

 Integrated LED spotlight, white RAL 9016, compact and minimalist design, low glare, dark-light detail for increased accentuation and visual comfort, ideal for museum, gallery and high-end retail applications, diecast aluminium body, passive cooling heatsink, beam angle: 37° medium beam, optics: Aluminium reflector, colour temperature: 4000K neutral white, total system power: 21W, total fixture output: 1528lm, luminaire efficacy: 73lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only. horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x169mm, weight: 0.96kg.

#### **Product Overview**

| Product name                      | BEACON ACCENT 97CRI 4K MEDIUM BEAM L3<br>ON-BOARD DIM WHITE |
|-----------------------------------|---|
| Technology                        | LED   |
| Cap/Base                          | N/A   |
| Housing                           | Aluminium   |
| Mount                             | Track mounting  |
| Environment                       | Internal  |
| General application               | Museums & Galleries, Retail                                 |
| ETIM Class                        | EC001744  |
| Fixture luminous flux (lm)        | 1528  |
| Luminaire efficacy (lm/W)         | 73  |
| LOR (%)                           | 100   |
| Correlated colour temperature (k) | 4000  |




## Concord

# BEACON ACCENT 97CRI 4K MEDIUM BEAM L3 ON-BOARD DIM WHITE **2059565**

| Light colour                | Neutral White      |
|-----------------------------|--------------------|
| CRI (Ra)                    | 97                 |
| Colour Consistency (SDCM)   | 3                  |
| Beam Angle (°)              | 37                 |
| Photobiological Risk Group  | RG1                |
| Total power consumption (W) | 21                 |
| Electrical protection       | Class II           |
| Control gear type           | Electronic ballast |
| Minimum dimming level (%)   | 5                  |
| Housing colour              | White              |
| IP rating                   | IP20               |
| IK rating                   | IK02               |
| Product EAN number          | 5025768595655      |
| Warranty                    | 5 years            |
| Dimming method              | 1-10V (Analogue)   |
| Useful luminous flux (#use) | 1528               |
|                             |                    |

### **Photometry**



### **Technical drawings**

