


START SURFACE IP66 1250LM 840 IK10 BLK
0049927



Features

- LED exterior surface mounted luminaire, 1250lm, 12W power consumption, 104lm/W efficacy, 4000K color temperature, CRI80, non-dimmable, IP66, IK10, 90,000 hours (L70B50) Lifespan, black housing, vandal resistant, supplied with anti-theft screws


Product Overview

Product name	START SURFACE IP66 1250LM 840 IK10 BLK
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor, Outdoor
General application	Hospitality
ETIM Class	EC002892
E-number FI	4579598
Fixture luminous flux (lm)	1250
Luminaire efficacy (lm/W)	105
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	RAL9011

START SURFACE IP66 1250LM 840 IK10 BLK 0049927

IP rating	IP66
IK rating	IK10
Product EAN number	5410288499277
Warranty	5 years
Dimming method	N/A
Useful luminous flux (#use)	1250

Photometry



Technical drawings

