



Features

- 50,000 hours average rated lifetime Last 2.5 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles – 200,000X High lumen efficacy Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast Works only with compatible electronic ballasts Ideal for factories, parking lots, supermarkets, department stores, schools and offices

Product Overview

Product name	ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
Technology	LED
Watt (Rated) (W)	26
Lamp shape	Tube, double-ended
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	26
Power consumption (W)	26
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20

ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
0029269

Product EAN number	5410288292694
Warranty	5 years
Useful luminous flux (#use)	3900

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
Technology	LED
Watt (Rated) (W)	26
Lamp shape	Tube, double-ended
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25

ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840 0029269

ETIM Class	EC001959
Warranty	5 years

OPTICAL DATA

Useful luminous flux (#use)	3900
Luminous flux (Rated) (lm)	3900
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	26
Wattage (W)	26
Primary Supply/Product voltage - min (V)	110
Primary Supply/Product voltage - max (V)	110
Ignition voltage (V)	80
Control gear required	Yes
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	35.2
Inrush Duration (µs)	421
Lamp Energy Label (class)	D
Max. products per 16A C Breaker	34
Max. products per 20A C Breaker	42
Max. products per 10A B Breaker	35
Max. products per 13A B Breaker	46
Max. products per 16A B Breaker	56



ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
0029269

LIFETIME DATA

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

PHYSICAL DATA

IP rating	IP20
Nominal Product Length (mm)	1462
Nominal Product Diameter (mm)	17
Weight (kg)	0.17

PACKAGING


Product EAN number	5410288292694
Packaging single length / height (cm)	146.2
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (inner)	15410288292691
Units per outer package	10
Packaging outer length / height (cm)	152.1
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	7.8

SAFETY DATA

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Safety message	None

ToLEDo Superia T5 ECG HO V3 5FT 3900LM 840
0029269


Energy label



26
kWh/1000h



2019/2015



26
kWh/1000h



2019/2015