


GIOTTO 335 3000K RECESSED MW SENSOR
3034807



Features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2225lm, 20.3W, 110lm/W, 3000K, CRI 80, non-dimmable, integral microwave sensor. 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.


Product Overview

Product name	GIOTTO 335 3000K RECESSED MW SENSOR
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Logistics & Industry
ETIM Class	EC002892
E-number FI	4225708
Fixture luminous flux (lm)	2225
Luminaire efficacy (lm/W)	110
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	20.3

GIOTTO 335 3000K RECESSED MW SENSOR
3034807


Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971348078
Warranty	5 years
Dimming method	N/A
Colour Code	830

Photometry



GIOTTO 335 3000K RECESSED MW SENSOR
3034807

Technical drawings



Data table

GENERAL DATA

Product name	GIOTTO 335 3000K RECESSED MW SENSOR
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Logistics & Industry
Operating temperature range (°C)	-25°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4225708
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2225
Luminaire efficacy (lm/W)	110
Correlated colour temperature (k)	3000
Colour Code	830
Light colour	Warm White

GIOTTO 335 3000K RECESSED MW SENSOR 3034807

CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	80

ELECTRICAL DATA

Total power consumption (W)	20.3
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.92
THD (at 230 V, 50 Hz, full load, at 100% dimming level) < xx.x %	15
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	No
Dimming method	N/A
Drive current (mA)	600
Inrush Current (A)	40
Inrush Duration (µs)	400
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	52
Max. products per 16A C Breaker	30
Max. products per 20A C Breaker	104
Max. products per 10A B Breaker	31
Max. products per 16A B Breaker	18

GIOTTO 335 3000K RECESSED MW SENSOR 3034807

Max. products per 20A B Breaker	62
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B10	120000
Lifespan L80 B50	120000
Lifespan L90 B50	74500

PHYSICAL DATA

Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	110
Nominal Product Diameter (mm)	355
Built-in diameter (mm)	335
Weight (kg)	1.2
Recessed Depth (mm)	41

PACKAGING

Product EAN number	8711971348078
Packaging single length / height (cm)	35.7
Packaging single width (cm)	35.7
Packaging single depth (cm)	10.6
DUN14 (inner)	08711971348078
Units per outer package	1
Packaging outer length / height (cm)	35.7
Packaging outer width (cm)	35.7
Packaging outer depth (cm)	10.6



GIOTTO 335 3000K RECESSED MW SENSOR
3034807

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-25-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No