


Concord

Solstice 200 2300lm 930 SSC01D SB
2070241



Features

- The Solstice 200 2300lm 930 SSC SBis a high efficient SSC SBdimmmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 3000K Warm White, Class II, Protection rating IP40/IP20, Cut out dimensions: 200mm.


Product Overview

Product name	Solstice 200 2300lm 930 SSC01D SB
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Retail
ETIM Class	EC001744
E-number FI	4262075
Fixture luminous flux (lm)	2300
Luminous flux (lm)	2300
Luminaire efficacy (lm/W)	135
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	70
Glare control	< 19

Solstice 200 2300Im 930 SSC01D SB
2070241

Photobiological Risk Group	RG1
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9005
IP rating	IP40/20
IK rating	IK02
Product EAN number	5025768702411
Warranty	5 years
Dimming method	SylSmart SSC
Useful luminous flux (#use)	2300

Photometry



Technical drawings

