



Features

- A range of high performance ToLEDo Superia T8 LED tubes with reminiscent look of fluorescent tubes High performance glass construction design High lumen output, with an impressive lumen efficacy of 185 lm/W Omnidirectional light distribution and wide beam angle Average rated life of 75,000 hours Lamp length - 1500mm High power factor 200,000 switching cycle 5 years warranty for complete peace of mind Compatible with electromagnetic gear / CCG and also suitable for direct mains operation (220-240V) No bending or discoloration over time Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots, waterproof luminaires and maintenance free applications

Product Overview

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Product name                      | ToLEDo SUPERIA T8 CCG L1500 4100LM 840 75K PET SL         |
| Technology                        | LED                                                       |
| Lamp shape                        | Tube, double-ended                                        |
| Cap/Base                          | G13                                                       |
| Lamp finish                       | Frosted/Coated                                            |
| General application               | Hospitality, Logistics & Industry, Residential & Consumer |
| ETIM Class                        | EC001959                                                  |
| E-number FI                       | 4941354                                                   |
| Correlated colour temperature (k) | 4000                                                      |
| CRI (Ra)                          | 80                                                        |
| Colour Variation Initial (SDCM)   | 6                                                         |
| Beam Angle (°)                    | 170                                                       |
| Photobiological Risk Group        | RG0                                                       |
| Wattage (W)                       | 22.2                                                      |
| Power consumption (W)             | 22.2                                                      |

ToLEDo SUPERIA T8 CCG L1500 4100LM 840 75K PET SL  
0030249

|                             |                             |
|-----------------------------|-----------------------------|
| Control gear type           | LED driver constant current |
| Housing colour              | White                       |
| IP rating                   | IP20                        |
| Product EAN number          | 5410288302492               |
| Warranty                    | 5 years                     |
| Dimming method              | N/A                         |
| Useful luminous flux (#use) | 4100                        |

Technical drawings

