


ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840
0029267



Features

- 50,000 hours average rated lifetime Last 2.5 times longer than 35W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles – 200,000X High lumen efficacy Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast Works only with compatible electronic ballasts Ideal for factories, parking lots, supermarkets, department stores, schools and offices

Product Overview

Product name	ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840
Technology	LED
Watt (Rated) (W)	18
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	18
Power consumption (W)	18
Control gear type	Electronic ballast
Dimmable	No

ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840
0029267

Average life (Nominal) (h)	50000
Housing colour	White
IP rating	IP20
Product EAN number	5410288292670
Warranty	5 years
Dimming method	N/A
Useful luminous flux (#use)	2800

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840
Technology	LED
Watt (Rated) (W)	18
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open

ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840 0029267

General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	5 years

OPTICAL DATA

Useful luminous flux (#use)	2800
Luminous flux (Rated) (lm)	2800
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	18
Wattage (W)	18
Current (A)	215
Primary Supply/Product voltage - min (V)	150
Primary Supply/Product voltage - max (V)	150
Ignition voltage (V)	105
Control gear required	Yes
Control gear type	Electronic ballast
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A



ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840
0029267

Inrush Current (A)	12.6
Inrush Duration (µs)	422
Lamp Energy Label (class)	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	48
Max. products per 20A C Breaker	60
Max. products per 10A B Breaker	48
Max. products per 13A B Breaker	65
Max. products per 16A B Breaker	80

LIFETIME DATA

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

PHYSICAL DATA

Housing colour	White
IP rating	IP20
Nominal Product Length (mm)	1462
Nominal Product Diameter (mm)	17
Weight (kg)	0.16

PACKAGING

Product EAN number	5410288292670
Packaging single length / height (cm)	146.0
Packaging single width (cm)	2.0
Packaging single depth (cm)	2.0
DUN14 (inner)	15410288292677
Units per outer package	10
Packaging outer length / height (cm)	152.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0


SAFETY DATA

ToLEDo Superia T5 ECG HE V3 5FT 2800LM 840
0029267

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	None

Energy label

**ENERG**⚡
SYLVANIA
0029267




18
kWh/1000h



2019/2015

**ENERG**⚡
SYLVANIA
0029267



18
kWh/1000h



2019/2015