



Features

- Reflector replacement modules for Otao Linear reflector versions, 3000K/4000K LED light source included, matte silver finishing, 4 modules per pack.

Product Overview

Product name	OTAO LINEAR REF SIL 4PCS
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
General application	Office, Education
ETIM Class	EC002556
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 19
Photobiological Risk Group	RG1
Electrical protection	Class III
Dimmable	No
Housing colour	RAL9003
IP rating	IP20
IK rating	IK03

OTAO LINEAR REF SIL 4PCS
0041808

Product EAN number	5410288418087
Warranty	5 years
Dimming method	N/A

Data table

GENERAL DATA	
Product name	OTAO LINEAR REF SIL 4PCS
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
General application	Office, Education
Operating temperature range (°C)	5°C...+50°C
ETIM Class	EC002556
Warranty	5 years

OPTICAL DATA	
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

ELECTRICAL DATA	
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Electrical protection	Class III
Control gear required	No
Dimmable	No
Dimming method	N/A

OTAO LINEAR REF SIL 4PCS 0041808

Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	100000

PHYSICAL DATA

Housing colour	RAL9003
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Diffuser material	Other
Reflector finish	Not Applicable
Weight (kg)	0.25

PACKAGING

Product EAN number	5410288418087
Packaging single length / height (cm)	29.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	13.0
DUN14 (inner)	15410288418084
Units per outer package	100
Packaging outer length / height (cm)	31.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	29.5

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-50
Special purpose lamp	No
Dry applications use only	No



OTAO LINEAR REF SIL 4PCS

0041808

Suitable for household illumination

No