

## ToLEDo T8 V7 5FT 2700LM 840 RL **0029298**



#### **Features**

• Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lampsOmnidirectional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubesHigh lumen package - 2700lmHigh lumen efficacy - 106 lm/WSwitching cycles - 200,000XAverage life 40,000 hours lifespanLamp length - 1500mmWide beam angleHigh power factorSuitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applicationsSuitable for operation with electromagnetic gears / CCG and direct mains operation (220-240V)3-Year warranty

#### **Product Overview**

| Product name                      | ToLEDo T8 V7 5FT 2700LM 840 RL                   |
|-----------------------------------|--|
| Technology                        | LED  |
| Watt (Rated) (W)                  | 25.5   |
| Lamp shape                        | Tube, double-ended                               |
| Cap/Base                          | G13  |
| Lamp finish                       | Opal   |
| Fixture rating                    | Open   |
| General application               | Hospitality, Logistics & Industry, Residential & |
|                                   | Consumer   |
| ETIM Class                        | EC001959   |
| E-number FI                       | 4941317  |
| Correlated colour temperature (k) | 4000   |
| Light colour                      | Cool White                                       |
| CRI (Ra)                          | 80   |
| Colour Variation Initial (SDCM)   | 6  |
| Beam Angle (°)                    | 170  |
| Photobiological Risk Group        | RG0  |



# ToLEDo T8 V7 5FT 2700LM 840 RL **0029298**

| Wattage (W)                 | 25.5          |
|-----------------------------|---------------|
| Power consumption (W)       | 25.5          |
| Dimmable                    | No            |
| Average life (Nominal) (h)  | 40000         |
| IP rating                   | IP20          |
| Product EAN number          | 5410288292984 |
| Warranty                    | 3 years       |
| Useful luminous flux (#use) | 2700          |

### **Technical drawings**

