


GIOTTO 235 3000K SURFACE 1-10V
3034757



Features

- Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1075lm, 10.1W, 106lm/W, 3000K, CRI 80, 1-10V dimmable, 120,000 hours lumen maintenance (L70:B50). Drive current: 275mA, IP44, IK10, Class I, 220-240V.


Product Overview

Product name	GIOTTO 235 3000K SURFACE 1-10V
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor
General application	Hospitality, Logistics & Industry
ETIM Class	EC002892
E-number FI	4270072
Fixture luminous flux (lm)	1075
Luminaire efficacy (lm/W)	106
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	10.1

GIOTTO 235 3000K SURFACE 1-10V
3034757


Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971347576
Warranty	5 years
Dimming method	1-10V (Analogue)
Colour Code	830

Photometry



GIOTTO 235 3000K SURFACE 1-10V
3034757

Technical drawings



Data table

GENERAL DATA

Product name	GIOTTO 235 3000K SURFACE 1-10V
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor
General application	Hospitality, Logistics & Industry
Operating temperature range (°C)	-25°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4270072
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	1075
Luminaire efficacy (lm/W)	106
Correlated colour temperature (k)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80

GIOTTO 235 3000K SURFACE 1-10V 3034757

Colour Variation Initial (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	80

ELECTRICAL DATA

Total power consumption (W)	10.1
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	1-10V (Analogue)
Drive current (mA)	300
Inrush Current (A)	5
Inrush Duration (µs)	50
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	52
Max. products per 16A C Breaker	85
Max. products per 20A C Breaker	104
Max. products per 10A B Breaker	31
Max. products per 16A B Breaker	50
Max. products per 20A B Breaker	62
Connectable conductor cross section - Min (mm²)	0.75

GIOTTO 235 3000K SURFACE 1-10V 3034757

Connectable conductor cross section - Max (mm²)	2.5
---	-----

LIFETIME DATA

Lifespan L70 B10	120000
Lifespan L80 B50	120000
Lifespan L90 B50	73500

PHYSICAL DATA

Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	92
Nominal Product Diameter (mm)	235
Weight (kg)	0.86

PACKAGING

Product EAN number	8711971347576
Packaging single length / height (cm)	26.5
Packaging single width (cm)	26.5
Packaging single depth (cm)	9.5
DUN14 (inner)	08711971347576
Units per outer package	1
Packaging outer length / height (cm)	26.5
Packaging outer width (cm)	26.5
Packaging outer depth (cm)	9.5

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-25-25
Special purpose lamp	No



GIOTTO 235 3000K SURFACE 1-10V
3034757

Dry applications use only	No
Suitable for household illumination	No