



Features

- LED Striplight replacement for incandescent lamp
- High lumen output: up to 806lm
- 15,000 hours average rated life
- Up to 85% energy saving
- Creates a warm ambiance similar to traditional lamps
- Perfect for kitchen, mirror lighting, shaver lighting, bathroom
- 3 year warranty


Product Overview

Product name	ToLEDo Striplight V3 300MM 450LM S14s
Technology	LED
Watt (Rated) (W)	5
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4741150
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Wattage (W)	5
Power consumption (W)	5
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288281056

ToLEDo Striplight V3 300MM 450LM S14s
0028105

Warranty	3 years
Useful luminous flux (#use)	450

Technical drawings



Data table

GENERAL DATA	
Product name	ToLEDo Striplight V3 300MM 450LM S14s
Technology	LED
Watt (Rated) (W)	5
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959

ToLEDo Striplight V3 300MM 450LM S14s 0028105

E-number FI	4741150
Warranty	3 years

OPTICAL DATA

Useful luminous flux (#use)	450
Luminous flux (Rated) (lm)	450
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	5
Wattage (W)	5
Equivalent watt (W)	35
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	1
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	2.4
Inrush Duration (µs)	200
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	460
Max. products per 13A C Breaker	598

ToLEDo Striplight V3 300MM 450LM S14s 0028105

Max. products per 16A C Breaker	67
Max. products per 20A C Breaker	920
Max. products per 16A B Breaker	33

LIFETIME DATA

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Length (mm)	298
Nominal Product Diameter (mm)	48
Weight (kg)	0.078

PACKAGING

Product EAN number	5410288281056
Packaging single length / height (cm)	30.7
Packaging single width (cm)	5.0
Packaging single depth (cm)	3.0
DUN14 (inner)	15410288281053
Units per outer package	6
Packaging outer length / height (cm)	31.3
Packaging outer width (cm)	10.6
Packaging outer depth (cm)	10.1

SAFETY DATA


Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

ToLEDo Striplight V3 300MM 450LM S14s
0028105

Energy label



0028105




5
kWh/1000h



2019/2015



0028105



5
kWh/1000h



2019/2015