

Features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 7600lm; 55W; 138lm/W; 3000K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.


Product Overview

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Product name                      | Resisto 1500 IP66 7600lm 830                              |
| Technology                        | LED                                                       |
| Cap/Base                          | N/A                                                       |
| Housing                           | PC Polycarbonate                                          |
| Mount                             | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application               | Logistics & Industry                                      |
| ETIM Class                        | EC002892                                                  |
| E-number FI                       | 4357054                                                   |
| Fixture luminous flux (lm)        | 7600                                                      |
| Luminaire efficacy (lm/W)         | 138                                                       |
| Correlated colour temperature (k) | 3000                                                      |
| CRI (Ra)                          | 80                                                        |
| Colour Consistency (SDCM)         | 5                                                         |
| Colour Variation Initial (SDCM)   | 5                                                         |
| Beam Angle (°)                    | 110                                                       |
| Glare control                     | < 25                                                      |
| Photobiological Risk Group        | RG1                                                       |
| Total power consumption (W)       | 55                                                        |
| Electrical protection             | Class I                                                   |

Resisto 1500 IP66 7600lm 830  
0010241


|                     |                             |
|---------------------|-----------------------------|
| Control gear type   | LED driver constant current |
| Dimmable            | No                          |
| LED Flickering Rate | Ultra low (5% or less)      |
| Housing colour      | Grey                        |
| IP rating           | IP66                        |
| IK rating           | IK08                        |
| Product EAN number  | 5410288102412               |
| Warranty            | 5 years                     |
| Dimming method      | N/A                         |

Photometry



Resisto 1500 IP66 7600lm 830  
0010241

Technical drawings



Data table

GENERAL DATA

|                                         |                                                           |
|-----------------------------------------|-----------------------------------------------------------|
| Product name                            | Resisto 1500 IP66 7600lm 830                              |
| Technology                              | LED                                                       |
| Cap/Base                                | N/A                                                       |
| Housing                                 | PC Polycarbonate                                          |
| Mount                                   | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application                     | Logistics & Industry                                      |
| Operating temperature range (°C)        | -20°C...+40°C                                             |
| Performance ambient temperature Tq (°C) | 25                                                        |
| ETIM Class                              | EC002892                                                  |
| E-number FI                             | 4357054                                                   |
| Warranty                                | 5 years                                                   |

OPTICAL DATA

|                            |      |
|----------------------------|------|
| Fixture luminous flux (lm) | 7600 |
|----------------------------|------|

## Resisto 1500 IP66 7600lm 830 0010241

|                                   |         |
|-----------------------------------|---------|
| Luminaire efficacy (lm/W)         | 138     |
| Correlated colour temperature (k) | 3000    |
| CRI (Ra)                          | 80      |
| Colour Variation Initial (SDCM)   | 5       |
| Colour Consistency (SDCM)         | 5       |
| Beam Angle (°)                    | 110     |
| Distribution type                 | Diffuse |
| Glare control                     | < 25    |
| Photobiological Risk Group        | RG1     |

### ELECTRICAL DATA

|                                                                  |                             |
|------------------------------------------------------------------|-----------------------------|
| Total power consumption (W)                                      | 55                          |
| Primary Supply/Product voltage - min (V)                         | 220                         |
| Primary Supply/Product voltage - max (V)                         | 240                         |
| Lamp power factor                                                | 0.95                        |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) < xx.x % | 20                          |
| Electrical protection                                            | Class I                     |
| Control gear required                                            | No                          |
| Control gear type                                                | LED driver constant current |
| No. Of switching cycles before premature failures                | >50000                      |
| Dimmable                                                         | No                          |
| Dimming method                                                   | N/A                         |
| Drive current (mA)                                               | 350                         |
| Inrush Current (A)                                               | 16                          |
| Inrush Duration (µs)                                             | 40                          |
| Nominal Frequency (Hz)                                           | 50/60Hz                     |
| LED Flickering Rate                                              | Ultra low (5% or less)      |
| Max. products per 10A C Breaker                                  | 24                          |
| Max. products per 13A C Breaker                                  | 32                          |
| Max. products per 16A C Breaker                                  | 39                          |
| Max. products per 20A C Breaker                                  | 49                          |
| Max. products per 10A B Breaker                                  | 24                          |
| Max. products per 13A B Breaker                                  | 32                          |

## Resisto 1500 IP66 7600lm 830 0010241

|                                                                 |     |
|-----------------------------------------------------------------|-----|
| Max. products per 16A B Breaker                                 | 39  |
| Max. products per 20A B Breaker                                 | 49  |
| Connectable conductor cross section -<br>Max (mm <sup>2</sup> ) | 2.5 |

### LIFETIME DATA

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 69000  |
| Lifespan L90 B10 | 31000  |

### PHYSICAL DATA

|                             |                  |
|-----------------------------|------------------|
| Housing colour              | Grey             |
| IP rating                   | IP66             |
| IK rating                   | IK08             |
| Diffuser finish             | Frosted          |
| Diffuser material           | PC Polycarbonate |
| Nominal Product Length (mm) | 1500             |
| Nominal Product Width (mm)  | 87               |
| Nominal Product Height (mm) | 80               |
| Weight (kg)                 | 1.95             |

### PACKAGING

|                                       |                |
|---------------------------------------|----------------|
| Product EAN number                    | 5410288102412  |
| Packaging single length / height (cm) | 150.5          |
| Packaging single width (cm)           | 10.0           |
| Packaging single depth (cm)           | 8.5            |
| DUN14 (inner)                         | 05410288102412 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 150.5          |
| Packaging outer width (cm)            | 10.0           |
| Packaging outer depth (cm)            | 8.5            |

### SAFETY DATA



Resisto 1500 IP66 7600lm 830  
**0010241**

|                                     |        |
|-------------------------------------|--------|
| Glow Wire Test (°C)                 | 850    |
| Optimal operating condition (°C)    | -20-40 |
| Special purpose lamp                | No     |
| Dry applications use only           | No     |
| Suitable for household illumination | No     |