



Features

- 50,000 hours average rated lifetime Last 2.5 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles - 200,000X Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Only suitable for direct mains (AC 220-240V) operation Ideal for factories, parking lots, supermarkets, department stores, schools and offices Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

Product Overview

Product name	ToLEDo SUPERIA T5 AC V2 5FT 5600LM 840
Technology	LED
Watt (Rated) (W)	37
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer
ETIM Class	EC001959
E-number FI	4941334
Luminous flux (lm)	5600
Correlated colour temperature (k)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	37
Power consumption (W)	37
Average life (Nominal) (h)	50000



ToLEDo SUPERIA T5 AC V2 5FT 5600LM 840
0029260

IP rating	IP20
Product EAN number	5410288292601
Warranty	5 years
Useful luminous flux (#use)	5600

Technical drawings

