

Concord

COLOSSAL 1200mm 840 PRISM DIR+HAL WHITE SSC

2071320



Features

- 1200mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct/indirect (halo) light distribution, 16665lm luminous flux, 117.5W system power, 142lm/W luminaire efficacy. Sylsmart Standalone enabled. Colour rendering index Ra >80, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40/IP20, IK03. 350mA drive current. UGR≤19. Electrical protection Class I, 220-240V. Reported lifetime 66k hours L90B10.

Product Overview


Product name	COLOSSAL 1200mm 840 PRISM DIR+HAL WHITE SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	16665
Luminaire efficacy (lm/W)	142
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	117.5
Electrical protection	Class I

Concord

COLOSSAL 1200mm 840 PRISM DIR+HAL WHITE SSC 2071320

Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP40/20
IK rating	IK07
Product EAN number	5025768713202
Warranty	5 years
Dimming method	SylSmart SSC
Colour Code	840

Photometry



Technical drawings

