



Features

- X-shape connection unit for opal diffuser version of Otao Linear range, RAL9003 (white) finishing, direct distribution, only 3000K/4000K LED light sources included, feed by next straight luminaire, shipped with 4x fast connectors and additional replacement electrical connectors, 50mm wide extruded aluminium profile, nominal size: 290x290x50x73mm.

Product Overview

Product name	OTAO LINEAR CORN-X OPAL 830/840 WH
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended
General application	Office, Education
ETIM Class	EC002556
E-number FI	4170600
Fixture luminous flux (lm)	1400
Luminaire efficacy (lm/W)	143
Correlated colour temperature (k)	4000
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	110
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	9.8
Electrical protection	Class III

OTAO LINEAR CORN-X OPAL 830/840 WH
0041811

Dimmable	No
Housing colour	RAL9003
IP rating	IP20
IK rating	IK03
Product EAN number	5410288418117
Warranty	5 years
Dimming method	N/A

Technical drawings

