

Features

- Integrated LED highbay; Black aluminium housing; 19500 Lm; 120 W; 163 Lm/W; 4000K; Drive current: 2350mA; CRI 80; 85° beam angle; Sylsmart SSA - Connected; IP54; Lifespan L80:B20 92,000 hrs; suspension wires included. Lampshades cannot be used for Granit SSA luminaires, as it disturbs the signal for the sensor.


Product Overview

Product name	Sylvania GRANIT IP54 19500LM 840 WB SSA
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4357112
Fixture luminous flux (lm)	19500
Luminaire efficacy (lm/W)	163
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	120
Electrical protection	Class I
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL9017
IP rating	IP54

Sylvania GRANIT IP54 19500LM 840 WB SSA 0039770

IK rating	IK08
Product EAN number	5410288397702
Warranty	5 years
Dimming method	SylSmart SSA

Photometry



Technical drawings

