



Features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent candle lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating

Product Overview

Product name	ToLEDo CANDLE V6 470LM 840 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740659
Luminous flux (lm)	470
Correlated colour temperature (k)	4000
CRI (Ra)	80
Beam Angle (°)	180
Wattage (W)	5
Power consumption (W)	5
Average life (Nominal) (h)	15000
Product EAN number	5410288275154
Warranty	3 years
Useful luminous flux (#use)	470

Data table

ToLEDo CANDLE V6 470LM 840 E14 SL 0027515

GENERAL DATA

Product name	ToLEDo CANDLE V6 470LM 840 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740659
Warranty	3 years

OPTICAL DATA

Useful luminous flux (#use)	470
Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Correlated colour temperature (k)	4000
CRI (Ra)	80
Beam Angle (°)	180
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	5
Wattage (W)	5
Starting time (max) (s)	0.5
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.5
Control gear required	No
Inrush Current (A)	3
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	138



ToLEDo CANDLE V6 470LM 840 E14 SL
0027515

Max. products per 16A C Breaker	222
Max. products per 20A C Breaker	278

LIFETIME DATA

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	35
Weight (kg)	0.026

PACKAGING

Product EAN number	5410288275154
Packaging single width (cm)	3.5
Packaging single depth (cm)	3.5
DUN14 (inner)	15410288275151
Units per inner package	6
Packaging inner length / height (cm)	11.5
Packaging inner width (cm)	8.0
Packaging inner depth (cm)	11.5
DUN14 (outer)	25410288275158
Packaging outer length / height (cm)	42.5

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	No
Safety message	Not Suitable for totally enclosed fixtures