

KubiXx 4000K 24KLM WIDE DALI
0062123



Features

- Logistics and Industry high bay luminaire with wide optics to provide homogenous light distribution for open space areas. 24400lumens, 140W, 174lm/W, 4000K, CRI80, wide beam optic, DALI-2 dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK06.


Product Overview

Product name	KubiXx 4000K 24KLM WIDE DALI
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	24400
Luminaire efficacy (lm/W)	174
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 23
Photobiological Risk Group	RG1
Total power consumption (W)	140
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Grey
IP rating	IP65

KubiXx 4000K 24KLM WIDE DALI
0062123

IK rating	IK06
Product EAN number	5410288621234
Warranty	5 years
Dimming method	DALI-2

Photometry



Technical drawings

