Concord

NILO 800 DIR/INDIR 3K DALI WHITE **2050600**





Features

Nilo is a 360° curve-shaped luminaire with a striking, minimalistic design, perfect for retail, hospitality, and office environments The product can be suspended at different hights to create appealing lighting effects Stand-alone and self contained lighting fixture Aluminium body, opal diffuser, emits direct and indirect lighting Textured white finishing colour Light color temperature: 3000K, warm white System power: 53W Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation DALI dimmable, 220-240V / 50-60Hz 80% direct, and 20% indirect lighting Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Nominal product dimensions: diameter 800mmx65mm

Product Overview

Product name	NILO 800 DIR/INDIR 3K DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Retail, Museums & Galleries
ETIM Class	EC002892
Fixture luminous flux (lm)	5700
Luminaire efficacy (Im/W)	108
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG0




Concord

NILO 800 DIR/INDIR 3K DALI WHITE **2050600**

Total power consumption (W)	53
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5025768506002
Warranty	5 years
Dimming method	DALI
Useful luminous flux (#use)	5700

Photometry



Technical drawings

