

START Downlight Flat 205 IP44 2200LM 830 DIM
0054124



Features

- START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate phase dimmable driver and Loop in out box; 24W; 2200Lm; 92Lm/W; 3000K; IP44 rated from the front.




Product Overview

Product name	START Downlight Flat 205 IP44 2200LM 830 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278501
Fixture luminous flux (lm)	2200
Luminaire efficacy (lm/W)	92
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	24
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9003

START Downlight Flat 205 IP44 2200LM 830 DIM 0054124

IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541242
Warranty	5 years
Dimming method	Mains: leading / trailing edge
Useful luminous flux (#use)	2200

Photometry



Technical drawings

