SAFETY DATA SHEET

In accordance with 1907/2006 annex II and 1272/2008 (All references to EU regulations and directives are abbreviated into only the numeric term) Amendment date 2024-08-19 Replaces SDS issued 2024-07-26 Revision date 2023-06-14 Version number 2.2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name MAUS Stixx Pro

UFI: YK6H-F1DD-A00H-0FPS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fire extinguishing agents

1.3. Details of the supplier of the safety data sheet

Company MAUS Sweden AB

Sockerbruksgatan 20 531 40 Lidköping

Sweden

Telephone 08-12 00 51 30 E-mail info@maussafety.com

1.4. Emergency telephone number

Phone number for emergencies: 999 or 112. The numbers are available 24/7.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Ox. Sol. 2, H272 Skin Irrit. 2, H315 Skin. Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373

(See section 16)

2.2. Label elements

Hazard pictogram



Signal word	Danger
Hazard statements	
H272	May intensify fire; oxidiser
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs (urinary tract) through prolonged or repeated exposure
Precautionary statements	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking
P220	Keep away from clothing and other combustible materials
P260	Do not breathe dust
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves, protective clothing and eye or face protection
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+P313	If skin irritation or rash occurs: Get medical advice/attention
P405	Store locked up
P501	Dispose of contents and container to authorised waste disposal facility

Supplemental hazard information

Contains: STRONTIUM NITRATE, MELAMINE, FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH PHENOL

2.3. Other hazards

This product does not contain any substances that are assessed to be a PBT or a vPvB Contains substance on the candidate list of Substances of Very High Concern.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Note that the table shows known hazards of the ingredients in pure form. These hazards are reduced or eliminated when mixed or diluted, see Section 16d.

Constituent	Classification	Concentration
POTASSIUM NITRATE		
CAS No: 7757-79-1 EC No: 231-818-8 REACH: 01-2119488224-35	Ox. Sol. 3; H272	50 - 75 %
STRONTIUM NITRATE		
CAS No: 10042-76-9 EC No: 233-131-9	Ox. Sol. 1, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H271, H315, H319, H335	20 - 35 %
MELAMINE		
CAS No: 108-78-1 EC No: 203-615-4 Index No: 613-345-00-2	Carc. 2, STOT RE 2; H351, H373	10 - 20 %
FORMALDEHYDE, OLIG	OMERIC REACTION PRODUCTS WITH PHENOL	
CAS No: 9003-35-4 EC No: 500-005-2	Skin. Sens. 1; H317	5 - 15 %

Explanations to the classification and labelling of the ingredients are given in Section 16e. Official abbreviations are printed in normal font. Text in italics are specifications and/or complements used in the calculation of the classification of this mixture, see Section 16b.

SECTION 4: First aid measures

4.1. Description of first aid measures

Generally

Normally, the product constitutes no risk as long as the cover remains intact. First aid measures mentioned below only apply in case of exposure to the product content.

If exposed or concerned: Get medical advice/attention.

Never attempt to administer liquid, or anything else, to an unconscious person via the mouth.

Upon breathing in

Move casualty to fresh air and rinse nose, mouth and throat with water.

Please contact the doctor.

Upon eye contact

Remove contact lenses immediately if possible.

Rinse the eye for several minutes with lukewarm water. If irritation persists call a doctor/ophthalmologist.

Upon skin contact

Remove contaminated clothes.

Wash the skin with soap and water.

Contact a doctor.

Wash/clean clothes with large amounts of water, to reduce fire hazard.

Upon ingestion

Rinse mouth out thoroughly first with water, then SPIT OUT the rinse water. Drink at least half a litre of water and seek medical advice. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed Generally

Suspected to be able to cause cancer.

May cause damage to organs through prolonged or repeated exposure.

Upon breathing in

Irritation.

May cause respiratory irritation.

Upon eye contact

Irritation.

Upon skin contact

Irritation.

May cause an allergic skin reaction.

Burn injuries may occur during contact with heated product.

4.3. Indication of any immediate medical attention and special treatment needed

Actions under first aid and the stated symptoms are relevant for incorrect handling of the product causing exposure of the contents.

Symptomatic treatment.

Upon contact with a doctor, make sure to have the label or this safety data sheet with you.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended extinguishing agents

Extinguish with water mist, powder, carbon dioxide or alcoholresistant foam.

Unsuitable extinguishing agents

May not be extinguished with water dispersed under high pressure.

5.2. Special hazards arising from the substance or mixture

Oxidising agent. May intensify fire. The product itself is not flammable but can support fire, even in the absence of air. When heated, the product melts. At a higher temperature, decomposition takes place, whereby toxic gases such as nitrogen oxides are emitted. When heated in enclosed spaces, decomposition can lead to explosive processes.

Hazardous combustion products:.

- Carbon oxides.
- Nitrous gases (NOx).

5.3. Advice for firefighters

Protective measures to be taken with regard to other materials at the scene of the fire.

In case of fire use proper breathing apparatus.

Wear full protective clothing.

Cool closed containers that were exposed to fire with water.

Any extinguishing should be executed from a good distance due to the risk of violent reaction or explosion.

Evacuate all not-authorized personnel.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use recommended safety equipment, see section 8.

Upon larger spills, wear suitable protective gloves and eye protection, as well as fire resistant clothing.

Avoid inhalation and exposure to skin and eyes.

Ensure good ventilation.

Keep unauthorized and unprotected people at a safe distance.

In case of spillage in protected water, call the emergency services immediately, tel. 112 (in Europe).

Chemical protection suits should be worn for all salvage and decontamination work.

6.2. Environmental precautions

Avoid release to drains, soil or watercourses.

Please contact involved authorities if unintended release occurs.

6.3. Methods and material for containment and cleaning up

Collect spillage in sealable containers and send for disposal. Clean up residue with an appropriate solvent and ventilate the facilty with fresh air.

6.4. Reference to other sections

See section 8 and 13 for personal protection equipment and disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Take the necessary preventive and protective measures for safe handling.

Read and follow the instructions for handling.

Must be handled with care to avoid puncture or damage to the product.

Consider the risk of violent chemical reactions.

Do not use damaged or partially damaged products.

Do not inhale the smoke.

Avoid contact with skin and eyes.

Store this product separately from food items and keep it out of the reach of children and pets.

Do not eat, drink or smoke in premises where this product is handled.

Wash your hands after using the product.

Remove contaminated clothing.

Wash contaminated clothing before reuse.

Keep away from incompatible products.

Use recommended safety equipment, see section 8.

Implement appropriate engineering controls if necessary, see Section 8.

7.2. Conditions for safe storage, including any incompatibilities

The product should be stored in a manner which prevents hazards to health and the environment. Avoid exposure to humans and animals and do not discharge the product in a sensitive environment.

Take the necessary preventive and protective measures for safe storage.

Keep out of reach for children.

To be stored away from food and animal fodder and away from devices or surfaces that are in contact with those items.

Store tightly, in original packaging.

Store in dry and cool area.

Store in a well-ventilated space.

Do not store close to incompatible materials (see section 10.5).

7.3. Specific end use(s)

See identified uses in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National limit values

Dust

United Kingdom (EH40/2005)

Time-weighted-average exposure limit (TWA) 10 mg/m³ (Inhalable dust) / 4 mg/m³ (Respirable dust)

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

The risks posed by the product or its constituents must be considered in the task specific risk assessment, in accordance with current working environment legislation. The risk assessment should be reviewed regularly and updated if necessary.

8.2.1. Appropriate engineering controls

The ventilation in the workplace must ensure an air quality that meets the requirements of the current working environment legislation. Local exhaust ventilation should be used to remove airborne contaminants at the source.

Eye/face protection

Use protective glasses with tight seals according to standard EN166.

Skin protection

Follow current local regulations for recommending protective gloves.

Use protective gloves fulfilling the standard EN374 if there is a risk of direct contact.

During continuous contact use gloves with a minimum breakthrough time of at least 240 minutes, preferably over 480 minutes.

The most suitable protective glove should be chosen in consultation with the glove supplier, taking into account the risk assessment for the specific task and the properties of the chemicals involved. Note that the breakthrough time of the material is affected by the duration of the exposure, temperature conditions, abrasion, etcetera.

Respiratory protection

Use an appropriate breathing apparatus for mist forming applications.

The most appropriate respiratory protective equipment should be decided in consultation with the appointed safety representative, taking into account the risk assessment for the specific task.

Based on the physical and chemical properties of the product, the following filter type(s) and/or filter combination(s) are recommended:.

-P2.

Breathing apparatus may be required.

8.2.3. Environmental exposure controls

Work with the product should take place in such a way that the product does not get into drains, waterways, soil and air.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(a) Physical state solid

Form: solid
(b) Colour
(c) Odour
(d) Melting point/freezing point
(e) Boiling point or initial boiling point and boiling range
(f) Flammability
(g) Lower and upper explosion limit
(h) Flash point
Not indicated
Not indicated
Not indicated

(i) Auto-ignition temperature >500 °C (j) Decomposition temperature Not indicated

(k) pH In working solution the pH value is: 7.5

(l) Kinematic viscosity Not indicated

(m) Solubility Solubility in water: Soluble

(n) Partition coefficient n-octanol/water (log value)
 (o) Vapour pressure
 (p) Density and/or relative density
 (q) Relative vapour density
 (r) Particle characteristics
 Not indicated
 Not indicated
 Not indicated

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Not indicated

9.2.2. Other safety characteristics

Not indicated

SECTION 10: Stability and reactivity

10.1. Reactivity

May intensify fire. Oxidising.

10.2. Chemical stability

The product is stable at normal storage and handling conditions.

10.3. Possibility of hazardous reactions

Reacts with metals.

Reacts with reducing agent.

10.4. Conditions to avoid

Avoid heat, sparks and open flames.

Do not let a heated product come in contact with water or other liquids.

10.5. Incompatible materials

Avoid contact with metal powders (Al, Zn, Be, etc.).

Peroxides.

Titanium.

Fluorine and fluorine compounds.

Cyanides.

Sulphides.

Phosphorus.

Water.

Bases, reducing substances, combustible and organic materials, metal oxides, salts of metals.

Reducing agents.

Antimony.

10.6. Hazardous decomposition products

Does not decompose to hazardous substances.

SECTION 11: Toxicological information

The information in this section is only applicable in case of exposure to the product content.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on possible health hazards are based on experience and / or toxicological properties of several components in the product.

Acute toxicity

The product is not classified as acutely toxic.

POTASSIUM NITRATE

LD50 rat 24h: 3750 mg/kg Orally

STRONTIUM NITRATE

LD50 rat 24h: 2750 mg/kg Orally

Skin corrosion/irritation

Irritant to skin.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

The product is not classified as mutagen.

Carcinogenicity

Is suspected to be carcinogenic.

Reproductive toxicity

The product is not classified as a reproductive toxicant.

STOT-single exposure

May cause potent irritation in the airways/lungs.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Target organ(s):.

- urinary tract.

Aspiration hazard

The product is not classified as being toxic for aspiration.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No information is available.

11.2.2. Other information

Not indicated.

SECTION 12: Ecological information

12.1. Toxicity

The product is not to be labelled as a environmental hazard. However, it is not inconceivable that large emissions, or repeated small emissions, can have a harmful effect on the environment.

Prevent release on land, in water and drains.

POTASSIUM NITRATE

LC50 Guppy (Poecilia reticulata) 96h: 1378 mg/L

12.2. Persistence and degradability

There is no information regarding persistence or degradability.

12.3. Bioaccumulative potential

There is no information regarding bioaccumulation.

12.4. Mobility in soil

Information about mobility in nature is not available.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances that are assessed to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

No information is available.

12.7. Other adverse effects

No known effects or hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste handling of the product

Avoid discharge into sewers.

Discarded products must be disposed of as hazardous waste in accordance with regulations.

Not completely emptied packaging can contain remnants of dangerous substances and should therefore be handled as hazardous waste according to the above. Completely emptied packaging can be recycled.

See directive 2008/98/EC on waste. Observe national or regional provisions on waste management.

SECTION 14: Transport information

Where not otherwise stated the information applies to all of the UN Model Regulations, i.e. ADR (road), RID (railway), ADN (inland waterways), IMDG (sea), and ICAO (IATA) (air).

14.1. UN number or ID number

1477

14.2. UN proper shipping name

NITRATES, INORGANIC, N.O.S (POTASSIUM NITRATE, STRONTIUM NITRATE)

14.3. Transport hazard class(es)

Class

5.1: Oxidizing substances

Classification code (ADR/RID)

O2: Oxidizing substances without subsidiary risk or articles containing such substances: Solid

Subsidiary risk (IMDG)

No subsidary risk according to IMDG

Labels



14.4. Packing group

Packing group III

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Tunnel restrictions

Tunnel category: E

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8 Other transport information

Transport category: 3; Maximum total quantity per transport unit: 1000 kgs or litres (ADR 1.1.3.6) Stowage category not indicated (IMDG)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Contains substance on the candidate list of Substances of Very High Concern.

Substances on the list of SVHC Candidate List for authorisation (substances that meet the criteria in Article 57 of the REACH Regulation):

MELAMINE

CAS No: 108-78-1 EC No: 203-615-4 Index No: 613-345-00-2

15.2. Chemical safety assessment

Assessment and chemical safety report in accordance with 1907/2006 Annex I has not yet been performed.

SECTION 16: Other information

16a. Indication of where changes have been made to the previous version of the safety data sheet Revisions of this document

Earlier versions

Carc. 2

2024-07-26 Changes in section(s) 1.

16b. Legend to abbreviations and acronyms used in the safety data sheet Full texts for Hazard Class and Category Code mentioned in section 3

Ox. Sol. 3	Oxidising Solids, Hazard Category 3 - Ox. Sol. 3, H272 - May intensify fire; oxidiser
Ox. Sol. 1	Oxidising Solids, Hazard Category 1 - Ox. Sol. 1, H271 - May cause fire or explosion; strong oxidiser

Skin Irrit. 2 Skin corrosion/irritation, Hazard Category 2 - Skin Irrit. 2, H315 - Causes skin irritation

Eye Irrit. 2 Serious eye damage/eye irritation, Hazard Category 2 - Eye Irrit. 2, H319 - Causes serious eye irritation STOT SE 3 Specific target organ toxicity — Single exposure, Hazard Category 3, Respiratory tract irritation - STOT SE 3, H335 - May cause respiratory irritation

Carcinogenicity, Hazard Category 2 - Carc. 2, H351 - Suspected of causing cancer <state route of

exposure if it is conclusively proven that no other routes of exposure cause the hazard>

STOT RE 2 Specific target organ toxicity — Repeated exposure, Hazard Category 2 - STOT RE 2, H373 - May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>

Skin. Sens. 1 Respiratory or skin sensitisation, Sensitisation — Skin, hazard category 1 - Skin. Sens. 1, H317 - May cause an allergic skin reaction

Ox. Sol. 2 Oxidising Solids, Hazard Category 2 - Ox. Sol. 2, H272 - May intensify fire; oxidiser

Explanations of the abbreviations in Section 14

ADR European Agreement concerning the International Transport of Dangerous Goods by Road

RID Regulations concerning the International Transport of Dangerous Goods by Rail

IMDG International Maritime Dangerous Goods Code

ICAO International Civil Aviation Organization (ICAO, 999 University Street, Montreal, Quebec H3C 5H7, Canada)

IATA The International Air Transport Association

Tunnel restriction code: E; Passage through category E tunnels is strictly forbidden

Transport category: 3; Maximum total quantity per transport unit: 1000 kgs or litres (ADR 1.1.3.6)

16c. Key literature references and sources for data Sources for data

Primary data for the calculation of the hazards has preferentially been taken from the official European classification list, 1272/2008 Annex I, as updated to 2024-08-19.

Where such data was not available, alternative documentation used to establish the official classification was used, e.g. IUCLID (International Uniform Chemical Information Database). As a second alternative, information was used from reputable international chemical industries, and as a third alternative other available information was used, e.g. material safety data sheets from other suppliers or information from non-profit associations, where reliability of the source was assessed by expert opinion. If, in spite of this, reliable information could not be sourced, the hazards were assessed by expert opinions based on the known hazards of similar substances, and according to the principles in 1907/2006 and 1272/2008.

Full texts for Regulations mentioned in this Safety Data Sheet

1907/2006 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council

Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of

16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and

repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

EH40/2005 EH40/2005 Workplace exposure limits

2008/98/EC DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19

November 2008 on waste and repealing certain Directives

16d. Methods of evaluating information referred to in 1272/2008 Article 9 which was used for the purpose of classification

Hazard calculation for this mixture has been performed as a cumulative assessment with the aid of expert assessments in accordance with 1272/2008 Annex I , where all available information which may be significant to establishing the hazards of the mixture was assessed together, and in accordance with 1907/2006 Annex XI .

16e. List of relevant hazard statements and/or precautionary statements Full texts for hazard statements mentioned in section 3

- H272 May intensify fire; oxidiser
- H271 May cause fire or explosion; strong oxidiser
- H315 Causes skin irritation

1272/2008

- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H351 Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>
- H373 May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>
- H317 May cause an allergic skin reaction

16f. Advice on any training appropriate for workers to ensure protection of human health and the environment Warning for misuse

This product can cause harm if used improperly. The manufacturer, the distributor or the supplier are not responsible for adverse effects if the product is not handled in accordance with its intended use.

Other relevant information

Not indicated

Editorial information



This material safety data sheet has been prepared and checked by KemRisk®, KemRisk Sweden AB, Platensgatan 8, SE-582 20 Linköping, Sweden, www.kemrisk.se