# **ToLEDo AVANT T8 CCG L1500 2700LM** 865 50K RL

Item No: 0030244
















Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes High lumen package - 2700lm High lumen efficacy - 150 lm/W Switching cycles - 200,000X Average life 50,000 hours lifespan Lamp length - 1500mm Wide beam angle High power factor Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications Suitable for operation with electromagnetic gears / CCG and direct mains operation (220-240V) 5-Year warranty

# **Technical Assets**

Dimensions (mm)

**Photometrics** 



# **ToLEDo AVANT T8 CCG L1500 2700LM 865 50K RL**

Item No: 0030244



G	en	e۲	al	Y	at	a

Product name	ToLEDo AVANT T8 CCG L1500 2700LM 865 50K RL
Technology	LED
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C+55°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
E-number FI	4941349
Warranty	5 years

# **Optical data**

Useful luminous flux (Φuse)	2700
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0

#### **Electrical data**

Power consumption (W)	18
Wattage (W)	18
Current (A)	0.109
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
Dimmable	No
Inrush Current (A)	14.9
Inrush Duration (µs)	60
Lamp Energy Label (class)	D

#### Lifetime data

ifespan L70 B50	5000

# Physical data

IP rating	IP20
Nominal Product Length (mm)	1499
Nominal Product Diameter (mm)	28
Weight (kg)	0.227

### **Packaging**

Product EAN number	5410288302447
Packaging single length / height (cm)	155.2
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (inner)	15410288302444
Units per outer package	10
Packaging outer length / height (cm)	160.7
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	10.5

# Safety data

Optimal operating condition (°C)	-20-55
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture