

## PRODUCT DATASHEET

### QTP5 2X14...35

QUICKTRONIC® PROFESSIONAL 5 | ECG for FL 16 mm



---

#### Areas of application

- Emergency lighting systems acc. to EN 50172 / DIN VDE 0108-100
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Modernization of existing systems
- Suitable for luminaires of protection classes I and II

---

#### Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Perfect lamp start for applications with motion sensors
- Automatic restart after lamp replacement
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

---

#### Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lamp start with optimum filament preheating

- Lifetime: up to 100,000 h (temperature at  $T_c = 65\text{ °C}$ , max. 10 % failure rate)
- Energy Efficiency Index EEI: A2 BAT
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Safety: to EN 61347-2-3
- Lamp operation: to EN 60929

TECHNICAL DATA

Electrical data


Nominal wattage	78.00 W
Nominal voltage	220...240 V
Input voltage AC	198...264 V
Input voltage DC	176...276 V
U-OUT (working voltage)	330 V
Inrush current	24 A
Mains frequency	50/60 Hz
Max. ECG no. on circuit breaker 10 A (B)	12 <sup>1)</sup>
Max. ECG no. on circuit breaker 16 A (B)	19 <sup>1)</sup>
Operating frequency	40...50 kHz

1) Type B

Light technical data

Starting time	1 s
---------------	-----

Dimensions & Weight



Length	360.00 mm
Mounting hole spacing, length	350,0 mm
Width	30.00 mm
Height	21.00 mm
Product weight	234.00 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

### Lifespan

ECG lifetime	100000 h <sup>1)</sup>
--------------	------------------------

<sup>1)</sup> At T<sub>case</sub> = 65 °C at T<sub>c</sub> point / 10 % failure rate

### Capabilities

Dimmable	No
Max. cable length to lamp/LED module	2.0 m / 1.0 m
Suitable for fixtures with prot. class	I / II
Suitable for emergency lighting	Yes
End of lamp life safety shutdown	EOL T.2



### Certificates & Standards











Approval marks – approval	VDE / VDE-EMC / CE / ENEC 10
Standards	Acc. to EN 61347-2-3 / Acc. to EN 60929 / Acc. to EN 55015:2006 + A1:2007 / Acc. to EN 61000-3-2 / Acc. to EN 61547
Protection class	I/II
Type of protection	IP20
Energy efficiency class	A2 BAT
EEL – Energy Label	A2 BAT

### LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

### DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	334142_Technical guide - ECGs for T5-lamps
 Declarations of conformity	339525_Declaration of Conformity (GB)

Documents and certificates		Document name
	Certificates	335097_INOTEC
	Certificates	335128_VDE Quality Tested Simplified luminaire approbation
	Certificates	504210_VDE-EMC-Certificate QT5
	Certificates	335101_ENEC-VDE-Marks approval
	Certificates	335002_EMC-Marks approval
	Certificates	335098_CEAG
	Certificates	335169_Manufacturer's declaration – Lamp/ECG combinations: Frequent switching
	Certificates	554891_EAC PT family
	Product family datasheet	336478_Family data sheet QTP5
CAD/BIM files		Document name
	CAD data 3D PDF	313392_360x30x21 9900024

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321329073	Unpacked 1		234.00 g	
4008321329080	Shipping box 20	370 mm x 96 mm x 170 mm	4900.00 g	6.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.